



3875081 G E SOLID STATE

01E 11057 D

**U304-U306**



T-37-25

U304-U306

**ELECTRICAL CHARACTERISTICS** (Continued) ( $T_A = 25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter	Test Conditions			U304		U305		U306		Units
					Min	Max	Min	Max	Min	Max	
$C_{iss}$	Common-Source Input Capacitance (Note 2)	$V_{DS} = -15\text{V}$ , $V_{GS} = 0$			$f = 1\text{MHz}$						pF
$C_{rss}$	Common-Source Reverse Transfer Capacitance (Note 2)	$V_{DS} = 0$ , $V_{GS} = 12\text{V}$ (U304) $V_{GS} = 7\text{V}$ (U305), $V_{GS} = 5\text{V}$ (U306)				7		7		7	
$t_{d(on)}$	Turn-ON Delay Time (Note 2)		U304	U305	U306						ns
		$V_{DD}$	-10V	-6V	-6V		20		25		
$t_r$	Rise Time (Note 2)	$V_{GS(off)}$	12V	7V	5V		15		25		35
$t_{d(off)}$	Turn-OFF Delay Time (Note 2)	$R_L$	580 $\Omega$	743 $\Omega$	1800 $\Omega$		10		15		20
$t_f$	Fall Time (Note 2)	$V_{GS(on)}$	0	0	0		25		40		60
		$i_{D(on)}$	-15mA	-7mA	-3mA						

NOTES: 1. Pulse test pulsewidth=300 $\mu\text{s}$ , duty cycle $\leq$ 3%.  
 2. For design reference only, not 100% tested.

10

INTERSIL'S SOLE AND EXCLUSIVE WARRANTY OBLIGATION WITH RESPECT TO THIS PRODUCT SHALL BE THAT STATED IN THE WARRANTY ARTICLE OF THE CONDITION OF SALE. THE WARRANTY SHALL BE EXCLUSIVE AND SHALL BE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE.

NOTE: All typical values have been characterized but are not tested.