



CEM9435A



March 1998

P-Channel Enhancement Mode MOSFET

5

FEATURES

- -30V , -5.3A , $R_{DS(ON)}=50m\Omega$ @ $V_{GS}=-10V$.
 $R_{DS(ON)}=90m\Omega$ @ $V_{GS}=-4.5V$.
- Super high dense cell design for extremely low $R_{DS(ON)}$.
- High power and current handing capability.
- Surface Mount Package.



ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ\text{C}$ unless otherwise noted)

| Parameter | Symbol | Limit | Unit |
|---|----------------|------------|------------------|
| Drain-Source Voltage | V_{DS} | -30 | V |
| Gate-Source Voltage | V_{GS} | ± 20 | V |
| Drain Current-Continuous ^a @ $T_J=125^\circ\text{C}$ -Pulsed ^b | I_D | ± 5.3 | A |
| | I_{DM} | ± 20 | A |
| Drain-Source Diode Forward Current ^a | I_S | -1.9 | A |
| Maximum Power Dissipation ^a | P_D | 2.5 | W |
| Operating Junction and Storage Temperature Range | T_J, T_{STG} | -55 to 150 | $^\circ\text{C}$ |

THERMAL CHARACTERISTICS

| | | | |
|--|-----------------|----|--------------------|
| Thermal Resistance, Junction-to-Ambient ^a | $R_{\theta JA}$ | 50 | $^\circ\text{C/W}$ |
|--|-----------------|----|--------------------|

CEM9435A

ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

5

| Parameter | Symbol | Condition | Min | Typ ^c | Max | Unit |
|--|---------|---|-----|------------------|------|------|
| OFF CHARACTERISTICS | | | | | | |
| Drain-Source Breakdown Voltage | BVDSS | VGS=0V, ID=-250μA | -30 | | | V |
| Zero Gate Voltage Drain Current | IDSS | VDS=-24V, VGS=0V | | | -1 | μA |
| Gate-Body Leakage | IGSS | VGS=±20V, VDS=0V | | | ±100 | nA |
| ON CHARACTERISTICS^b | | | | | | |
| Gate Threshold Voltage | VGS(th) | VDS=VGS, ID = -250μA | -1 | | -3 | V |
| Drain-Source On-State Resistance | RDS(ON) | VGS = -10V, ID = -5.3A | | 40 | 50 | mΩ |
| | | VGS = -4.5V, ID = -4.2A | | 67 | 90 | mΩ |
| On-State Drain Current | ID(ON) | VDS = -5V, VGS = -10V | -20 | | | A |
| Forward Transconductance | gFS | VDS = -15V, ID = - 5.3A | 4 | 8.3 | | S |
| DYNAMIC CHARACTERISTICS^c | | | | | | |
| Input Capacitance | CISS | VDS=-15V, VGS = 0V f = 1.0MHz | | 860 | 1120 | pF |
| Output Capacitance | COSS | | | 458 | 600 | pF |
| Reverse Transfer Capacitance | CRSS | | | 140 | 190 | pF |
| SWITCHING CHARACTERISTICS^c | | | | | | |
| Turn-On Delay Time | tD(ON) | VD = -15V, ID = -1A, VGEN = - 10V, RGEN = 6Ω | | 9 | 30 | ns |
| Rise Time | tr | | | 16 | 60 | ns |
| Turn-Off Delay Time | tD(OFF) | | | 75 | 120 | ns |
| Fall Time | tf | | | 40 | 100 | ns |
| Total Gate Charge | Qg | VDS = -15V, ID = -5.3A, VGS = -10V | | 29 | 40 | nC |
| Gate-Source Charge | Qgs | | | 3 | | nC |
| Gate-Drain Charge | Qgd | | | 9 | | nC |

CEM9435A

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

| Parameter | Symbol | Condition | Min | Typ ^c | Max | Unit |
|---|----------|----------------------------|-----|------------------|------|------|
| DRAIN-SOURCE DIODE CHARACTERISTICS^b | | | | | | |
| Diode Forward Voltage | V_{SD} | $V_{GS} = 0V, I_S = -5.3A$ | | -0.84 | -1.3 | V |

5

Notes

- a. Surface Mounted on FR4 Board, $t \leq 10\text{sec}$.
- b. Pulse Test: Pulse Width $\leq 300\ \mu\text{s}$, Duty Cycle $\leq 2\%$.
- c. Guaranteed by design, not subject to production testing.




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Drain Current and Temperature

CEM9435A

5




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. Transconductance Variation with Drain Current




Figure 8. Body Diode Forward Voltage Variation with Source Current




Figure 9. Gate Charge




Figure 10. Maximum Safe Operating Area

CEM9435A




Figure 11. Switching Test Circuit




Figure 12. Switching Waveforms

5




Figure 13. Normalized Thermal Transient Impedance Curve