

TOSHIBA TRANSISTOR SILICON NPN TRIPLE DIFFUSED TYPE (PCT PROCESS)

2SC5356


SWITCHING REGULATOR APPLICATIONS
 HIGH VOLTAGE SWITCHING APPLICATIONS
 DC-DC CONVERTER APPLICATIONS

- Excellent Switching Times : $t_f = 0.5 \mu s$ (Max.) ($I_C = 1.2 A$)
- High Collectors Breakdown Voltage : $V_{CEO} = 800 V$
- High DC Current Gain : $h_{FE} = 15$ (Min.) ($I_C = 0.15 A$)

MAXIMUM RATINGS ($T_a = 25^\circ C$)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Base Voltage		V_{CB0}	900	V
Collector-Emitter Voltage		V_{CEO}	800	V
Emitter-Base Voltage		V_{EBO}	7	V
Collector Current	DC	I_C	3	A
	Pulse	I_{CP}	5	
Base Current		I_B	1	A
Collector Power Dissipation	$T_a = 25^\circ C$	P_C	1.5	W
	$T_c = 25^\circ C$		25	
Junction Temperature		T_j	150	$^\circ C$
Storage Temperature Range		T_{stg}	-55~150	$^\circ C$

Unit in mm



961001EAA1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current		ICBO	V _{CB} = 720 V, I _E = 0	—	—	100	μA
Emitter Cut-off Current		IEBO	V _{EB} = 7 V, I _C = 0	—	—	10	μA
Collector-Base Breakdown Voltage		V _{(BR)CBO}	I _C = 1 mA, I _B = 0	900	—	—	V
Collector-Emitter Breakdown Voltage		V _{(BR)CEO}	I _C = 10 mA, I _B = 0	800	—	—	V
DC Current Gain		h _{FE} (1)	V _{CE} = 5 V, I _C = 1 mA	10	—	—	
		h _{FE} (2)	V _{CE} = 5 V, I _C = 0.15 A	15			
Collector-Emitter Saturation Voltage		V _{CE(sat)}	I _C = 1.2 A, I _B = 0.24 A	—	—	1.0	V
Base-Emitter Saturation Voltage		V _{BE(sat)}	I _C = 1.2 A, I _B = 0.24 A	—	—	1.3	V
Switching Time	Rise Time	t _r	<p> $20 \mu s$ $V_{CC} = 360 V$ I_{B1} I_{B2} I_C INPUT OUTPUT 300Ω </p>	—	—	0.7	μs
	Storage Time	t _{stg}		—	—	4.0	
	Fall Time	t _f		$I_{B1} = 0.24 A, I_{B2} = -0.48 A$ $DUTY CYCLE \leq 1\%$	—	—	

