



TO-220

PIN CONFIGURATION
 1. BASE
 2. COLLECTOR
 3. EMITTER
 4. COLLECTOR



ALL DIMENSIONS ARE IN M.M.

DIM	MIN	MAX
A	14,42	16,51
B	9,63	10,67
C	3,56	4,83
D	—	0,90
E	1,15	1,40
F	3,75	3,88
G	2,29	2,79
H	2,54	3,43
J	—	0,56
K	12,70	14,73
L	—	6,35
M	2,03	2,92
N	—	31,24
O	7	DEG

TO-220 Power Package Transistors (NPN)

Maximum Ratings						Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)													
Type No.	V _{CE0} (V) Min	V _{CEO} (V) Min	V _{EB0} (V) Min	P ₀ (W) @Tc=25°C	I _C (A)	I _{CB0} (μA) Max	V _{CB} (V) @ (V)	I _{CES} (μA) Max	V _{CE} (V) @ (V)	h _{FE}	@	I _C & V _{CE} (A) (A) (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Min Max	I _C (A)	C _{ob} (pF) Max Typ	f _i (MHz) Min Typ Max	@	I _C (mA)
2N5294	80	70	7	36	4			#*500	50	30	120	0.5 4	1		0.5		0.8		200
2N5296	60	40	5	36	4			#*500	50	30	120	1 4	1		1		0.8		200
2N5298	80	60	5	36	4			#*500	50	20	80	1.5 4	1		1.5		0.8		200
2N6292	80	70	5	40	7			* 100	75	30	150	2 4	1		2	250	4		500
										2.3		7 4	3.5		7				
2SC1398	70	50	5	15	2	1	40			30		0.1 5	1		1.5 2				
										50	220	1 5							
2SC1398P	70	50	5	15	2	1	40			30		0.1 5	1		1.5 2				
										50	100	1 5							
2SC1398Q	70	50	5	15	2	1	40			30		0.1 5	1		1.5 2				
										80	160	1 5							
2SC1398R	70	50	5	15	2	1	40			30		0.1 5	1		1.5 2				
										120	200	1 5							
2SC2073	150	150	5	25	1.5	10	120			40	140	0.5 10	1.5		0.5	35	4		500
2SC2233	200	60	5	40	4	10	170			30	150	1 5	1		1.5 4		8		500
										20		4 5							
2SC2238	160	160	5	25	1.5	1	160			70	240	0.1 5	1.5		0.5	25	100		100
2SC2238O	160	160	5	25	1.5	1	160			70	140	0.1 5	1.5		0.5	25	100		100
2SC2238Y	160	160	5	25	1.5	1	160			120	240	0.1 5	1.5		0.5	25	100		100
2SC2335	500	400	7	40	7	10	400			20	80	0.1 5	1		1.2 3				
										20	80	1 5							
										10		3 5							
2SC2335O	500	400	7	40	7	10	400			20	80	0.1 5	1		1.2 3				
										30	60	1 5							
										10		3 5							

* NOTE : I_{CEX}
 #* NOTE : I_{CER}

2383394 0000998 899