

Low-Ripple, Low-Saturation CMOS Regulators Monolithic IC MM309X, MM310X Series

Outline

This is a voltage regulator IC developed using the CMOS process.

Use of the CMOS process allows low current consumption, and it has superior ripple rejection ratio and transient response compared to conventional CMOS process regulator ICs, making it ideal for use in portable communications devices.

Ceramic capacitors can be used for the output capacitors.

Ideal for small, portable devices as SOT-25 and WLCSP are used for the package.

Features

1. Super low consumption current	45µA typ. (when not loaded, excluding the CE terminal current)
2. Super low consumption current (when off)	0.1µA typ.
3. High precision output voltage	±2%
4. Output current	150mA
5. Input/output voltage difference	0.23V typ. ($I_{O}=100mA$, 3V output)
6. High ripple rejection ratio	80dB typ.
7. Built-in short-circuit restriction circuit	30mA typ.
8. Wide operating temperature range	-30~+85°C
9. Output voltage	1.8~5.0V (0.1V step)


Package

SOT-25, WLCSP-4 (MM309X),
WLCSP-5 (MM310X)


Applications

1. Constant voltage power supply for devices that use batteries
2. Constant voltage power supply for portable communications devices
3. Constant voltage power supply for household electronics products


Block Diagram




Pin Assignment



WLCSP-4
(BOTTOM VIEW)



SOT-25A
(TOP VIEW)



WLCSP-5
(BOTTOM VIEW)

1	GND
2	V _{OUT}
3	V _{DD}
4	CE

1	V _{OUT}
2	GND
3	V _{DD}
4	CE
5	V _{DD}

1	CE
2	GND
3	V _{OUT}
4	V _{DD}
5	NC

Pin Description

■ WLCSP-4

Pin No.	Pin name	Functions						
1	GND	GND pin						
2	V _{OUT}	Regulator output pin						
3	V _{DD}	Voltage-supply pin						
4	CE	ON/OFF-Control pin <table border="1"> <tr> <td>CE</td> <td>OUTPUT</td> </tr> <tr> <td>L</td> <td>OFF</td> </tr> <tr> <td>H</td> <td>ON</td> </tr> </table> Connect CE pin with V _{DD} pin, when it is not used.	CE	OUTPUT	L	OFF	H	ON
CE	OUTPUT							
L	OFF							
H	ON							

■ SOT-25A

Pin No.	Pin name	Functions						
1	V _{OUT}	Regulator output pin						
2	GND	GND pin						
3,5	V _{DD}	Voltage-supply pin						
4	CE	ON/OFF-Control pin <table border="1"> <tr> <td>CE</td> <td>OUTPUT</td> </tr> <tr> <td>L</td> <td>OFF</td> </tr> <tr> <td>H</td> <td>ON</td> </tr> </table> Connect CE pin with V _{DD} pin, when it is not used.	CE	OUTPUT	L	OFF	H	ON
CE	OUTPUT							
L	OFF							
H	ON							

■ WLCSP-5

Pin No.	Pin name	Functions						
1	CE	ON/OFF-Control pin <table border="1"> <tr> <td>CE</td> <td>OUTPUT</td> </tr> <tr> <td>L</td> <td>OFF</td> </tr> <tr> <td>H</td> <td>ON</td> </tr> </table> Connect CE pin with V _{DD} pin, when it is not used.	CE	OUTPUT	L	OFF	H	ON
CE	OUTPUT							
L	OFF							
H	ON							
2	GND	GND pin						
3	V _{OUT}	Regulator output pin						
4	V _{DD}	Voltage-supply pin						
5	NC							

Absolute Maximum Ratings (Ambient Temperature, Ta=25°C)

Item	Symbol	Ratings	Unit
Storage Temperature	T _{STG}	-55~+125	°C
Supply Voltage	V _{DD}	7	V
CE Input Voltage	V _{OUT}	-0.3~V _{DD} +0.3	V
Output Voltage	V _{OUT}	-0.3~V _{DD} +0.3	V
Output Current	I _{omax.}	200	mA
Power Dissipation	P _d	190	mW

Recommended Operating Conditions (Ambient Temperature, Ta=25°C)

Item	Symbol	Ratings	Unit
Operating Temperature	T _{jop}	-40~85	°C
Operating Voltage	V _{OP}	2~6	V
Output Current	I _o	0~150	mA

Electrical Characteristics (V_{DD}=V_{out} typ.+1V, V_{CE}=V_{DD}, Ta=25°C unless otherwise specified)

Item	Symbol	Measurement conditions	Min.	Typ.	Max.	Unit
Input Current(OFF)	I _{DDoff}	V _{CE} =0V		0.1	1.0	µA
No-Load Input Current	I _{DD}			45	100	µA
Output Voltage	V _{OUT}	1mA ≤ I _{OUT} ≤ 30mA	×0.98		×1.02	V
Line Regulation	V _L	V _{DD} =V _O typ.+0.5~6V I _{OUT} =30mA		0.05	0.20	%/V
Load Regulation	V _L	1mA ≤ I _{OUT} ≤ 80mA		20	45	mV
Dropout Voltage	V _{io}	Please refer to another page				V
Ripple Rejection *1	RR	Please refer to another page				dB
V _{out} Temperature Coefficient *1	Δ V _{OUT} /ΔT	I _{OUT} =10mA -40mA ≤ T _{OPT} ≤ 85°C		±100		ppm/°C
Output Short-Circuit Current *1	I _{lim}	V _O =0V		30		mA
CE Pull-down Resistance	R _{pd}		2.5	5	15	MΩ
CE High Threshold voltage	V _{CEH}		1.5		V _{DD}	V
CE Low Threshold voltage	V _{CEL}		0		0.25	V

Note: *1 design guaranteed.


Electrical Characteristics 2 ($V_{DD}=V_{OUT}$ typ.+1V, $V_{CE}=V_{DD}$ $T_a=25^\circ C$ unless otherwise specified)

Product Name	PARAMETER									
	Output Voltage			Dropout Voltage			Ripple Regulation*1			
	V_{OUT} (V)			V_{IO} (V)			RR (db)			
TEST CONDITIONS	MIN.	TYP.	MAX.	TEST CONDITIONS	TYP.	MAX.	TEST CONDITIONS	TYP.	MAX.	
MM3091J	1.764	1.800	1.836	*2 I _{OUT} =100mA 2.0 ≤ V _{OUT} ≤ 2.3	0.25	0.35	f=1kHz Vripple=0.5V 1.8 ≤ V _{OUT} ≤ 4.0	80	70	
MM3091K	1.862	1.900	1.938							
MM3092A	1.960	2.000	2.040							
MM3092B	2.058	2.100	2.142							
MM3092C	2.156	2.200	2.244							
MM3092D	2.254	2.300	2.346							
MM3092E	2.352	2.400	2.448							
MM3092F	2.450	2.500	2.550							
MM3092G	2.548	2.600	2.652							
MM3092H	2.646	2.700	2.754							
MM3092J	2.744	2.800	2.856							
MM3092K	2.842	2.900	2.958							
MM3093A	2.940	3.000	3.060							
MM3093B	3.038	3.100	3.162							
MM3093C	3.136	3.200	3.264							
MM3093D	3.234	3.300	3.366							
MM3093E	3.332	3.400	3.468							
MM3093F	3.430	3.500	3.570							
MM3093G	3.528	3.600	3.672							
MM3093H	3.626	3.700	3.774							
MM3093J	3.724	3.800	3.876							
MM3093K	3.822	3.900	3.978							
MM3094A	3.920	4.000	4.080							
MM3094B	4.018	4.100	4.182							
MM3094C	4.116	4.200	4.284							
MM3094D	4.214	4.300	4.386							
MM3094E	4.312	4.400	4.488							
MM3094F	4.410	4.500	4.590							
MM3094G	4.508	4.600	4.692							
MM3094H	4.606	4.700	4.794							
MM3094J	4.704	4.800	4.896							
MM3094K	4.802	4.900	4.998							
MM3095A	4.900	5.000	5.100							


Note: *1 design guaranteed.

Note: *2 The parameter is not guaranteed in the model less than $V_{OUT}=2V$.

Measuring Circuit



Application Circuits



*Temperature Characteristics: B

(reference example of external parts)

- Output Capacitor Ceramic Capacitor 2.2μF (Output voltage : 2.5~5.0V)
 - Input Capacitor Ceramic Capacitor 4.7μF (Output voltage : 1.8~2.5V)
 - Input Capacitor Ceramic Capacitor 2.2μF

Note

1. The output capacitor is required between output and GND to prevent oscillation.
 2. The ESR of capacitor must be defined in ESR stability area

It is possible to use a ceramic capacitor without ESR resistance for output.


The ceramic capacitor must be used more than $2.2\mu\text{F}$ or $4.7\mu\text{F}$ and B temperature characteristics.

3. The wire of VCC and GND is required to print full ground plane for noise and stability.


The input capacitor must be connected a distance of less than 1cm from input pin.

Characteristics (2.8V product Except where noted otherwise, Ta=25°C, V_{IN}=V_O+1V, V_{CES}=V_{DD}, C_{IN}=2.2μF, C_{OUT}=2.2μF)


Output Voltage




No-Load Input Current




Line Regulation




Load Regulation



Dropout Voltage




Current Limit




Characteristics (2.8V product Except where noted therwise, Ta=25°C, V_{IN}=V_O+1V, V_{CES}=V_{DD}, C_{IN}=2.2μF, C_O=2.2μF)


GND Pin Current




ESR



Output Voltage-Ambient Temperature




Ripple Rejection




Characteristics (2.8V product Except where noted otherwise, Ta=25°C, V_{IN}=V_O+1V, V_{CES}=V_{DD}, C_{IN}=2.2μF, C_O=2.2μF)

■ Rise Time (V_{CES}=0 → 2.0V)



■ Input Transient Response (V_{DD}=3.8V → 4.8V)



■ Load Transient Response (V_O=1mA → 100mA, C_O=2.2μF) ■ Load Transient Response (V_O=1mA → 100mA, C_O=1.0μF)

