



LOW VOLTAGE 4Ω SPDT SWITCH

- **HIGH SPEED:**
 $t_{PD} = 0.3 \text{ ns (TYP.) at } V_{CC} = 5V$
 $t_{PD} = 0.4 \text{ ns (TYP.) at } V_{CC} = 3.0V$
- **LOW POWER DISSIPATION:**
 $I_{CC} = 1 \mu A \text{ (MAX.) at } T_A = 85 \text{ }^\circ C$
- **LOW "ON" RESISTANCE:**
 $R_{ON} = 4\Omega \text{ (MAX. } T_a=25^\circ C) \text{ AT } V_{CC} = 5V$
 $R_{ON} = 6\Omega \text{ (TYP.) AT } V_{CC} = 3.0V$
- **WIDE OPERATING VOLTAGE RANGE:**
 $V_{CC} \text{ (OPR)} = 1.8V \text{ to } 5.5V \text{ SINGLE SUPPLY}$




ORDER CODES		
PACKAGE	TUBE	T & R
SOT23-6L		STG719FTR

DESCRIPTION

The STG719 is an high speed SPDT CMOS SWITCH frabricated in silicon gate C²MOS technology. It is designed to operate from 1.8V to 5.5V, making this device ideal for portable applications. It offers 4Ω ON-Resistance Max at

5V 25°C. Additional key features are fast switching speed ($t_{ON}=7ns, t_{OFF}=4.5ns$) and Low Power Consumption ($<0.01\mu W$ Typ.). ESD immunity is higher than 1000V per Method 3015.7 of MIL-STD-883B. It's available in the commercial temperature range.

PIN CONNECTION AND IEC LOGIC SYMBOLS



DC SPECIFICATIONS

Symbol	Parameter	Test Conditions		Value					Unit
		V _{CC} (V)		T _A = 25 °C			-40 to 85 °C		
				Min.	Typ.	Max.	Min.	Max.	
V _{IHC}	High Level Control Input Voltage	3.0 ^(*)		2.0			2.0		V
		5.0 ^(**)		2.4			2.4		
V _{ILC}	Low Level Control Input Voltage	3.0 ^(*)				0.4		0.4	V
		5.0 ^(**)				0.8		0.8	
R _{ON}	ON Resistance	3.0 ^(*)	V _S = 0 to V _{CC} I _S = 10 mA		6	7		10	Ω
		5.0 ^(**)				4		5	
ΔR _{ON}	ON Resistance Match Between Channels	3.0 ^(*)	V _S = 0 to V _{CC} I _S = 10 mA		0.1			0.4	Ω
		5.0 ^(**)			0.1			0.4	
R _{FLATON}	ON Resistance Flatness	3.0 ^(*)	V _S = 0 to V _{CC} I _S = 10 mA		2.5				Ω
		5.0 ^(**)			0.75				
I _{SOFF}	Source OFF Leakage	3.0 ^(*)	V _S = 1V or V _{CC} V _D = V _{CC} or 1V V _{IN} = V _{CC} or GND		±0.01	±0.25		±0.35	nA
		5.0 ^(**)			±0.01	±0.25		±0.35	
I _{SON}	Channel ON Leakage Current	3.0 ^(*)	V _S =V _D =1V to V _{CC} -2.5V V _{IN} = V _{IHC}		±0.01	±0.25		±0.35	nA
		5.0 ^(**)			±0.01	±0.25		±0.35	
I _{IN}	Control Input Leakage Current	3.0 ^(*)	V _I = V _{IH} or V _{IL}		0.005			±0.1	μA
		5.0 ^(**)			0.005			±0.1	
I _{CC}	Quiescent Supply Current	3.0 ^(*)	V _I = V _{CC} or GND		0.001			1	μA
		5.0 ^(**)			0.001			1	

(*) Voltage range is 3.0V ± 0.3V

(**) Voltage range is 5V ± 0.5V

AC ELECTRICAL CHARACTERISTICS (C_L = 35 pF, R_L = 300Ω)

Symbol	Parameter	Test Condition		Value					Unit
		V _{CC} (V)		T _A = 25 °C			-40 to 85 °C		
				Min.	Typ.	Max.	Min.	Max.	
t _{PD}	Delay Time	3.0 ^(*)	V _S = 3V square wave f=1MHz t _r =t _f =6ns		0.4	0.8		1.2	ns
		5.0 ^(**)			0.3	0.6		1.0	
t _{ON}	ON Channel Time	3.0 ^(*)	V _S = 2V		10			16	ns
		5.0 ^(**)	V _S = 3V		7			11	
t _{OFF}	OFF Channel Time	3.0 ^(*)	V _S = 2V		5.5			7	ns
		5.0 ^(**)	V _S = 3V		4.5			6	
t _D	Break Before Make Time Delay	3.0 ^(*)	V _S = 2V	1	4				ns
		5.0 ^(**)	V _S = 3V	1	4				
C _{SOFF}	OFF Channel Capacitance				19				pF
C _{SON}	ON Channel Capacitance				33				pF

(*) Voltage range is 3.0V ± 0.3V

(**) Voltage range is 5V ± 0.5V

ANALOG SWITCH CHARACTERISTICS ($C_L = 5\text{ pF}$, $R_L = 50\Omega$, $GND = 0\text{ V}$, $T_A = 25^\circ\text{C}$)


Symbol	Parameter	Test Condition		Value	Unit
		V_{CC} (V)			
f_{MAX}	Frequency Response (Switch ON)	3.0 ^(*)	Bandwidth at -3dB	200	MHz
		5.0 ^(**)		200	
OIRR	OFF Isolation (Switch OFF)	3.0 ^(*)	$f_{IN} = 10\text{MHz}$ sine wave	-40	dB
		3.0 ^(*)	$f_{IN} = 1\text{MHz}$ sine wave	-74	
		5.0 ^(**)	$f_{IN} = 10\text{MHz}$ sine wave	-40	
		5.0 ^(**)	$f_{IN} = 1\text{MHz}$ sine wave	-74	
	Crosstalk (Between Channels)	3.0 ^(*)	$f_{IN} = 10\text{MHz}$ sine wave	-39	dB
		3.0 ^(*)	$f_{IN} = 1\text{MHz}$ sine wave	-52	
		5.0 ^(**)	$f_{IN} = 10\text{MHz}$ sine wave	-39	
		5.0 ^(**)	$f_{IN} = 1\text{MHz}$ sine wave	-52	

(*) Voltage range is $3.0\text{V} \pm 0.3\text{V}$


(**) Voltage range is $5\text{V} \pm 0.5\text{V}$

TEST CIRCUITS


ON RESISTANCE




OFF LEAKAGE




ON LEAKAGE




OFF ISOLATION




BANDWIDTH




CHANNEL TO CHANNEL CROSSTALK



SWITCHING TIMES




BREAK BEFORE MAKE TIME DELAY



SOT23-6L MECHANICAL DATA

DIM.	mm			mils		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	0.90		1.45	35.4		57.1
A1	0.00		0.15	0.0		5.9
A2	0.90		1.30	35.4		51.2
b	0.35		0.50	13.7		19.7
C	0.09		0.20	3.5		7.8
D	2.80		3.00	110.2		118.1
E	2.60		3.00	102.3		118.1
E1	1.50		1.75	59.0		68.8
L	0.35		0.55	13.7		21.6
e		0.95			37.4	
e1		1.9			74.8	



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2000 STMicroelectronics – Printed in Italy – All Rights Reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia - Malta - Morocco
Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>