

TOSHIBA RECTIFIER SILICON DIFFUSED TYPE


U05GH44, U05JH44

HIGH SPEED RECTIFIER APPLICATIONS
(FAST RECOVERY)

- Repetitive Peak Reverse Voltage : $V_{RRM}=400, 600V$
- Average Forward Current : $I_F(AV)=0.5A$
- Reverse Recovery Time : $t_{rr}=1.5\mu s$
- Surface Mounting Plastic Mold Package

MAXIMUM RATINGS

CHARACTERISTIC		SYMBOL	RATING	UNIT
Repetitive Peak Reverse Voltage	U05GH44	V_{RRM}	400	V
	U05JH44		600	
Average Forward Current		$I_F(AV)$	0.5	A
Peak One Cycle Surge Forward Current (Non-Repetitive)		I_{FSM}	20 (50Hz)	A
Junction Temperature Range		T_j	-40~125	°C
Storage Temperature Range		T_{stg}	-40~125	°C




Weight : 0.06g


ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Peak Forward Voltage	V_{FM}	$I_{FM}=0.5A$	—	—	1.2	V
Repetitive Peak Reverse Current	I_{RRM}	$V_{RRM}=\text{Rated}$	—	—	10	μA
Reverse Recovery Time	t_{rr}	$I_F=20mA, I_R=1mA$	—	—	1.5	μs

STANDARD SOLDERING PAD



MARKING








CODE	TYPE
GH	U05GH44
JH	U05JH44

Month (Starting from Alphabet A)

Year (Last Number of the Christian Era)

961001EAA2

● TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.



961001EAA2'

● The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.

● The information contained herein is subject to change without notice.