



# KBPC300G THRU KBPC310G

## SINGLE PHASE 3.0 AMPS. GLASS PASSIVATED BRIDGE RECTIFIERS




### FEATURES

- \* Glass passivated junction
- \* Surge overload rating 60 amperes peak
- \* Low forward voltage drop
- \* Small size, simple installation
- \* Leads solderable per MIL-STD-202, method 208

**VOLTAGE RANGE**  
50 to 1000 Volts  
**CURRENT**  
3.0 Amperes

### KBPC-3



Dimensions in inches and (millimeters)

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.  
Single phase, half wave, 60 Hz, resistive or inductive load.  
For capacitive load, derate current by 20%

TYPE NUMBER	SYMBOLS	KBPC 300G	KBPC 301G	KBPC 302G	KBPC 304G	KBPC 306G	KBPC 308G	KBPC 310G	UNITS
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Bridge Input Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum D. C. Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current @ $T_C = 50^\circ C$	$I_{F(AV)}$	3.0							A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	60							A
Maximum Forward Voltage Drop per element @ 1.5A	$V_F$	1.10							V
Maximum Reverse Current at Rated @ $T_A = 25^\circ C$ D. C. Blocking Voltage per element @ $T_A = 125^\circ C$	$I_R$	10 500							$\mu A$ $\mu A$
Operating Temperature Range	$T_J$	- 55 to + 150							$^\circ C$
Storage Temperature Range	$T_{STG}$	- 55 to + 150							$^\circ C$

## RATINGS AND CHARACTERISTIC CURVES (KBPC300G THRU KBPC310G)

FIG. 1 - MAXIMUM NON - REPETITIVE FORWARD SURGE CURRENT - PER ELEMENT




FIG. 2 - TYPICAL FORWARD OUTPUT CURRENT DERATING CURVE




FIG. 3 - TYPICAL FORWARD CHARACTERISTICS - PER ELEMENT




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS - PER ELEMENT

