

Messrs. Rockwell Automation

SPECIFICATION

Device Name : IGBT Module
Type Name : 7MBR30SA060E-01
Spec. No. : MS6M 0543
Date : Jun. - 02 - 2000


This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

Fuji Electric Co., Ltd.
Matsumoto Factory


DATE	NAME	APPROVED	Fuji Electric Co., Ltd.	
DRAWN: Jan. - 2 - '00	J. Kobayashi	J. Hiyata	DWG. NO.	MS6M 0543
CHECKED: June - 2 - 00	S. Naito			

7MBR30SA060E-01

1. Outline Drawing (Unit : mm)



2. Equivalent circuit



Fuji Electric Co., Ltd.

DWG. NO.

MS6M 0543

3 / 10

H04-004-03

This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

3. Absolute Maximum Ratings (at Tc= 25C unless otherwise specified)

Items		Symbols	Conditions	Maximum Ratings	Units
Inverter	Collector-Emitter voltage	VCES		600	V
	Gate-Emitter voltage	VGES		+ -20	V
	Collector current	lc	Continuous	30	A
		lcp	1ms	60	A
		-lc		30	A
Collector Power Dissipation	Pc	1 device	120	W	
Brake	Collector-Emitter voltage	VCES		600	V
	Gate-Emitter voltage	VGES		+ -20	V
	Collector current	lc	Continuous	20	A
		lcp	1ms	40	A
	Collector Power Dissipation	Pc	1 device	80	W
	Repetitive peak reverse Voltage(Diode)	VRRM		600	V
Converter	Repetitive peak reverse Voltage	VRRM		800	V
	Average Output Current	Io	50Hz/60Hz sine wave	50	A
	Surge Current (Non-Repetitive)	IFSM	Tj= 150C, 10ms	350	A
	I ² t (Non-Repetitive)	I ² t	half sine wave	613	A ² s
Junction temperature		Tj		150	C
Storage temperature		Tstg		-40~ +125	C
Isolation voltage	between terminal and copper base ^(*)1)	Viso	AC : 1min.	2500	V
	between thermistor and others ^(*)2)			2500	V
Mounting Screw Torque ^(*)3)				3.5	Nm

(*1) All terminals should be connected together when isolation test will be done.

(*2) Terminal 8 and 9 should be connected together. Terminal 1 to 7 and 10 to 24 should be connected together and shorted to copper base.

(*3) Recommendable Value : 2.5~3.5 Nm (M5)

Fuji Electric Co.,Ltd.

DWG. NO.

MS6M 0543

4 / 10

H04-004-03

4. Electrical characteristics (at Tj= 25C unless otherwise specified)

Items	Symbols	Conditions	Characteristics			Units			
			min.	typ.	Max.				
Inverter	Zero gate voltage Collector current	ICES	VGE	0 V, VCE	600 V		1.0	mA	
	Gate-Emitter leakage current	IGES	VCE	0 V, VGE	+20 V		200	nA	
	Gate-Emitter threshold voltage	VGE(th)	VCE	20 V, Ic =	30 mA	5.5	7.8	8.5	V
	Collector-Emitter saturation voltage	VCE(sat)	VGE	15 V, chip			1.8		V
			Ic =	30 A terminal			1.95	2.4	
	Input capacitance	Cies	VGE	0 V, VCE	10 V		3000		pF
	Turn-on time	ton	Vcc =	300 V			0.45	1.2	us
		tr	Ic =	30 A			0.25	0.6	
		tr(β)	VGE	+15 V			0.08		
	Turn-off time	toff	RG =	82 ohm			0.40	1.0	us
tf						0.05	0.35		
Forward on voltage	VF	IF =	30 A	chip		1.8		V	
				terminal		1.95	2.6		
Reverse recovery time	trr	IF =	30 A				300	ns	
Brake	Zero gate voltage Collector current	ICES	VGE	0 V, VCE	600 V		1.0	nA	
	Gate-Emitter leakage current	IGES	VCE	0 V, VGE	+20 V		200	nA	
	Collector-Emitter saturation voltage	VCE(sat)	VGE	15 V, chip			1.8		V
			Ic =	20 A terminal			1.95	2.4	
	Turn-on time	ton	Vcc =	300 V			0.45	1.2	us
		tr	Ic =	20 A			0.25	0.6	
	Turn-off time	toff	VGE	+15 V			0.40	1.0	us
tf		RG =	120 ohm			0.05	0.35		
Reverse current	IRRM	VR =	600 V				1.0	mA	
Converter	VFM	IF =	30 A	chip		1.0		V	
				terminal		1.1	1.5		
Reverse current	IRRM	VR =	800 V				1.0	mA	
Thermistor	Resistance	R	T = 25C			5000		ohm	
			T = 100C		465	495	520		
	B value	B	T = 25/50C			3305	3375	3450	K

5. Thermal resistance characteristics

Items	Symbols	Conditions	Characteristics			Units
			min.	typ.	Max.	
Thermal resistance (1 device)	Rth(j-c)	Inverter IGBT			1.04	C/W
		Inverter FWD			2.00	
		Brake IGBT			1.56	
		Converter Diode			0.90	
Contact Thermal resistance	Rth(c-f)	with Thermal Compound (*)		0.05		C/W

* This is the value which is defined mounting on the additional cooling fin with thermal compound.

Fuji Electric Co.,Ltd.

DWG.NO.


MS6M 0543

5/10

H04-004-03

This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

6. Indication on module




7. Applicable category

This specification is applied to Power Integrated Module named 7MBR30SA060E-01.

8. Storage and transportation notes







- The module should be stored at a standard temperature of 5 to 35°C and humidity of 45 to 75% .
- Store modules in a place with few temperature changes in order to avoid condensation on the module surface.
- Avoid exposure to corrosive gases and dust.
- Avoid excessive external force on the module.
- Store modules with unprocessed terminals.
- Do not drop or otherwise shock the modules when transporting.
- Please connect adequate fuse or protector of circuit between three-phase line and this product to prevent the equipment from causing secondary destruction.

9. Definitions of switching time



This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd.

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.









Fuji Electric Co., Ltd.

DWG. NO.

MS6M 0543

7 / 10

This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party or used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.



Fuji Electric Co., Ltd.

DWG. NO.


MS6M 0543

8 / 10


H04-004-03

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.


[Inverter]
Forward current vs. Forward on voltage (typ.)




[Inverter]
Reverse recovery characteristics (typ.)
 $V_{cc} = 300V, V_{GE} = \pm 15V, R_g = 82\Omega$




[Converter]
Forward current vs. Forward on voltage (typ.)



Transient thermal resistance



[Thermistor]
Temperature characteristic (typ.)



Fuji Electric Co., Ltd

DWG. NO.


MS6M 0543

9 / 10


H04-004-03

This material and the information herein is the property of Fuji Electric Co. Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd.


[Brake]
Collector current vs. Collector-Emittor voltage
 $T_j = 25^\circ\text{C}$ (typ.)




[Brake]
Collector current vs. Collector-Emittor voltage
 $T_j = 125^\circ\text{C}$ (typ.)




[Brake]
Collector current vs. Collector-Emittor voltage
 $V_{GE} = 15\text{V}$ (typ.)




[Brake]
Collector-Emittor voltage vs. Gate-Emittor voltage
 $T_j = 25^\circ\text{C}$ (typ.)



[Brake]
Capacitance vs. Collector-Emittor voltage (typ.)
 $V_{GE} = 0\text{V}$, $f = 1\text{MHz}$, $T_j = 25^\circ\text{C}$



[Brake]
Dynamic Gate charge (typ.)
 $V_{CC} = 300\text{V}$, $I_c = 20\text{A}$, $T_j = 25^\circ\text{C}$



Fuji Electric Co., Ltd.

DWG. NO.

MS6M 0543

10 / 10

H04-004-03

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.