



| | | |
|-----------------------------------------------------------|----------------------|---------------------------------------------------------------------------------------------|
| STK4703 SERIES | thick film hybrid IC | CIRCUIT DRAWING No.6026 |
| 2-CHANNEL 10 TO 50W MIN AF POWER AMP.(DUAL-SUPPLY) | |  4029 |

Features


- AF Output Power

| | | |
|------------------|------------------|------------------|
| STK4773: 10Wmin. | STK4793: 15Wmin. | STK4803: 20Wmin. |
| STK4813: 20Wmin. | STK4833: 25Wmin. | STK4843: 30Wmin. |
| STK4853: 30Wmin. | STK4863: 35Wmin. | STK4873: 35Wmin. |
| STK4893: 40Wmin. | STK4913: 50Wmin. | |
- Contains emitter follower circuit for upgrading.
- Case temperature 125°C is guaranteed, thereby enabling great reduction of heat sink.
- By attaching muting circuit externally, pop noise at the time of power ON/OFF can be rejected.

| | | |
|-------------------------------------------------------|----------------------|-----------------------------------------------------------------------------------------------------------------|
| STK5320 SERIES | thick film hybrid IC | CIRCUIT DRAWING No.6028 |
| 2-OUTPUT SERIES REGULATOR FOR VTR APPLICATIONS | |  4036 4037 4039 |


Features

- | | | | | |
|-----------|------------------|------------------|------------------|------------------|
| | STK5321 | STK5322 | STK5324 | STK5325 |
| Output 1: | 9.5±0.1V (1.6A) | 9.5±0.1V (1.6A) | 12.0±0.1V (1.6A) | 12.0±0.1V (1.6A) |
| Output 2: | 12.0±0.3V (2.5A) | 15.0±0.3V (2.5A) | 12.0±0.3V (2.5A) | 14.0±0.3V (2.5A) |
| | STK5326 | STK5327 | | |
| Output 1: | 12.0±0.1V (1.6A) | 15.0±0.3V (2.5A) | | |
| Output 2: | 13.0±0.3V (2.5A) | 13.5±0.3V (1.6A) | | |
- 2-output/1-package voltage regulator fabricated using Sanyo's original IMST (Insulated Metal Substrate Technology).
- Provides cutoff function to cut off output voltage by external signal.
- Output voltages of 2 outputs are set.
- Small size and excellent cost performance.
- Package Number: 4036 (STK5324)
4037 (STK5325, 5326, 5327)
4039 (STK5321, 5322)

| | | |
|-------------------------------------------------------|----------------------|-----------------------------------------------------------------------------------------------|
| STK5346 | thick film hybrid IC | CIRCUIT DRAWING No.6027 |
| 2-OUTPUT SERIES REGULATOR FOR VTR APPLICATIONS | |  4038 |

Features

- 2-output/1-package voltage regulator fabricated using Sanyo's original IMST (Insulated Metal Substrate Technology).
- Provides cutoff function to cut off output voltage by external signal.
- Output voltages of 2 outputs are set.
- Small size and excellent cost performance.

| | | |
|-------------------------------------------------------|----------------------|-----------------------------------------------------------------------------------------------|
| STK5352,5353 | thick film hybrid IC | CIRCUIT DRAWING No.6029 |
| 2-OUTPUT SERIES REGULATOR FOR VTR APPLICATIONS | |  4064 |

Features

- | | | |
|-----------|------------------|------------------|
| | STK5352 | STK5353 |
| Output 1: | 6.0±0.1V (0.5A) | 5.1±0.1V (0.5A) |
| Output 2: | 12.0±0.1V (1.5A) | 12.0±0.1V (1.5A) |
- 2-output/1-package voltage regulator fabricated using Sanyo's original IMST (Insulated Metal Substrate Technology)
- Contains power supply for microcomputer.
- Output voltages of 2 outputs are set.
- Small size and excellent cost performance