


Features

- Wireless Interface Following the IEEE 802.11b Standard
- Wireless LAN MAC Unit with ARM7TDMI® RISC Processor
- Integrated 128-byte Transmit and 128-byte Receive FIFOs for Wireless MAC Layer Functions
- 16-bit PCMCIA Bus Interface
- Glueless SRAM Interface for All MAC Operations, Supporting up to 1M Byte of External Memory
- Integrated 6K x 32-bit Internal SRAM, Used for Fast Program Code Execution and Temporary Storage of Data
- Glueless Flash Memory Interface, Supporting up to 1M Byte of Nonvolatile Memory for Permanent Storage of Program Code
- Enciphering/Deciphering of Wireless Data On-the-fly by the Implementation of the Encryption/Decryption Code Ensures Maximum Privacy of Data
- The Integrated Physical Attachment Interface (PAI) Fully Supports Direct-sequence Spread Spectrum and Frequency-hopping Spread Spectrum (2 Mbps) Physical-layer Interfaces
- The WLAN and Inter-networking Functions can be Changed and Updated Easily to New Requirements Since They are Implemented in Microcode
- Supports 11 Mbps Rates with Automatic Fallback to 5.5, 2 and 1 Mbps
- 144-lead TQFP Package
- Low-voltage 3.3V Operation
- Internal ROM Contains Hardwired CIS Information for Automatic Configuration when Card is Inserted in the PCMCIA Slot or Reads Custom CIS Information from SPI Memory
- Offers SPI interface and 3 GPIO Pins
- AT76C502A Offers the Option to Download the Whole Code from SPI DataFlash® or an Option to Eliminate Flash by Downloading the Program from the Mass Storage Device

Block Diagram



11-megabit WLAN Media Access Controller (MAC)

AT76C502A Summary

1948DS-WLAN-09/03



Note: This is a summary document. A complete document is available under NDA. For more information, please contact your local Atmel sales office.


Description

Fast VirtualNet™ (AT76C502A) is a single-chip controller that provides all processing and functionality needed for the MAC protocol of wireless LANs (focusing on, but not limited to the IEEE 802.11b standard). AT76C502A provides a glueless interface conforming to PC Card 95 and can control a variety of physical interfaces.

The AT76C502A chip contains a PCMCIA bus interface, a MAC control unit and a physical attachment interface (PAI). The PAI supports direct-sequence spread spectrum and frequency-hopping spread spectrum (2 Mbps) physical interfaces, providing flexibility to end users.

The ARM7TDMI core supports two alternative instruction sets. Powerful 32-bit code can be executed by the processor in ARM® operating mode. However, a 16-bit instruction subset is also available in Thumb® mode. Thumb mode can be selected to exploit full processor power with limited external memory resources. Note that ARM7TDMI operating mode can be changed at run time with negligible overhead.

Functional Diagram





Atmel Corporation

2325 Orchard Parkway
San Jose, CA 95131, USA
Tel: 1(408) 441-0311
Fax: 1(408) 487-2600

Regional Headquarters

Europe

Atmel Sarl
Route des Arsenaux 41
Case Postale 80
CH-1705 Fribourg
Switzerland
Tel: (41) 26-426-5555
Fax: (41) 26-426-5500

Asia

Room 1219
Chinachem Golden Plaza
77 Mody Road Tsimshatsui
East Kowloon
Hong Kong
Tel: (852) 2721-9778
Fax: (852) 2722-1369

Japan

9F, Tonetsu Shinkawa Bldg.
1-24-8 Shinkawa
Chuo-ku, Tokyo 104-0033
Japan
Tel: (81) 3-3523-3551
Fax: (81) 3-3523-7581

Atmel Operations

Memory

2325 Orchard Parkway
San Jose, CA 95131, USA
Tel: 1(408) 441-0311
Fax: 1(408) 436-4314

Microcontrollers

2325 Orchard Parkway
San Jose, CA 95131, USA
Tel: 1(408) 441-0311
Fax: 1(408) 436-4314

La Chantrerie
BP 70602
44306 Nantes Cedex 3, France
Tel: (33) 2-40-18-18-18
Fax: (33) 2-40-18-19-60

ASIC/ASSP/Smart Cards

Zone Industrielle
13106 Rousset Cedex, France
Tel: (33) 4-42-53-60-00
Fax: (33) 4-42-53-60-01

1150 East Cheyenne Mtn. Blvd.
Colorado Springs, CO 80906, USA
Tel: 1(719) 576-3300
Fax: 1(719) 540-1759

Scottish Enterprise Technology Park
Maxwell Building
East Kilbride G75 0QR, Scotland
Tel: (44) 1355-803-000
Fax: (44) 1355-242-743

RF/Automotive

Theresienstrasse 2
Postfach 3535
74025 Heilbronn, Germany
Tel: (49) 71-31-67-0
Fax: (49) 71-31-67-2340

1150 East Cheyenne Mtn. Blvd.
Colorado Springs, CO 80906, USA
Tel: 1(719) 576-3300
Fax: 1(719) 540-1759

Biometrics/Imaging/Hi-Rel MPU/ High Speed Converters/RF Datacom

Avenue de Rochepleine
BP 123
38521 Saint-Egreve Cedex, France
Tel: (33) 4-76-58-30-00
Fax: (33) 4-76-58-34-80

Literature Requests

www.atmel.com/literature

Disclaimer: Atmel Corporation makes no warranty for the use of its products, other than those expressly contained in the Company's standard warranty which is detailed in Atmel's Terms and Conditions located on the Company's web site. The Company assumes no responsibility for any errors which may appear in this document, reserves the right to change devices or specifications detailed herein at any time without notice, and does not make any commitment to update the information contained herein. No licenses to patents or other intellectual property of Atmel are granted by the Company in connection with the sale of Atmel products, expressly or by implication. Atmel's products are not authorized for use as critical components in life support devices or systems.

© Atmel Corporation 2003. All rights reserved. Atmel® and combinations thereof, and DataFlash® are the registered trademarks of Atmel Corporation or its subsidiaries. ARM7TDMI®, ARM®, ARM7®, and Thumb® are the registered trademarks of ARM, Ltd.; AMBA™ is the trademark of ARM, Ltd. Other terms and product names may be the trademarks of others.



Printed on recycled paper.

1948DS-WLAN-09/03