



**SIEMENS****SUPER-RED HDN1131/1133O  
GREEN HDN1131/1133G****0.59" (13 mm) SEVEN SEGMENT NUMERIC DISPLAY  
LOW CURRENT**


T-41-33



Package Dimensions mm



HDN1131



HDN1133

**FEATURES**

- Current Consumption 2 mA
- Direct Drive by CMOS Microprocessor, Gate and LSTTL Modules
- Space Saving
- Lower Assembly Costs
- No Display and LED Driver Modules
- Good Readability in Unfavorable Lighting Conditions
- Climate-Proof
- High Packing Density
- Grey Package for Optimal Contrast
- Long Service Life
- Shock and Vibration Resistant
- Readable over Large Distances

**DESCRIPTION**

The HDN1131/1133 are one digit, seven segment, low current LED displays. The character height is 13 mm. The displays are available in super-red and green. Applications include state-of-the-art industrial and consumer electronics, especially where low current consumption is required, e.g. portable appliances and battery-operated appliances.

**Maximum Ratings**

Total Power Dissipation per Segment or Dot <sup>1)</sup> ( $T_A=80^\circ\text{C}$ ) ( $P_{TOT}$ ) .....	.....	.....	20 mW
Operating and Storage Temperature Range ( $T_{OP}$ , $T_{STO}$ ) .....	.....	.....	-40°C to +85°C
Forward Current per Segment or Dot <sup>1)</sup> ( $I_F$ ) .....	.....	.....	7 mA
Surge Current per Segment <sup>1)</sup> ( $I_F \leq 10 \mu\text{s}$ , $D \leq 0.005$ ) ( $I_{PM}$ ) .....	.....	.....	150 mA
Reverse Voltage ( $V_R$ ) .....	.....	.....	5 V
Thermal Resistance ( $R_{THA}$ ) .....	.....	.....	115 K/W
Junction Temperature ( $T_J$ ) .....	.....	.....	100°C

**Characteristics ( $T_A=25^\circ\text{C}$ )**

Parameter	Symbol	Super-Red	Green	Unit
Wavelength at Peak Emission ( $I_F=2 \text{ mA}$ )	$\lambda_{PEAK}$	635	565	nm
Dominant Wavelength ( $I_F=2 \text{ mA}$ )	$\lambda_{DOM}$	628	567	nm
Spectral Bandwidth @ 50% $I_V$ ( $I_F=2 \text{ mA}$ )	$\Delta_\lambda$	45	25	nm
Forward Voltage ( $I_F=2 \text{ mA}$ )	$V_F$	1.8 ( $\leq 2.6$ )	1.9 ( $\leq 2.6$ )	V
Reverse Current per Segment ( $V_R=5 \text{ V}$ )	$I_R$	0.01 ( $\leq 10$ )	0.01 ( $\leq 10$ )	$\mu\text{A}$
Capacitance per Segment ( $V_R=0 \text{ V}$ , $f=1 \text{ MHz}$ )	$C_0$	3	15	pF
Switching Times ( $I_F=25 \text{ mA}$ , $t_s=1 \mu\text{s}$ )				
Rise Time from 10% to 90%	$t_R$	200	450	ns
Fall Time from 90% to 10%	$t_f$	150	200	ns
Luminous Intensity per Segment <sup>2)</sup> ( $I_F=2 \text{ mA}$ )	$I_V$	600	600	$\mu\text{cd}$

**Notes:**1 This value applies to an ambient temperature of  $T_A \leq 80^\circ\text{C}$ 2 Deviation of the absolute values within one digit  $\frac{I_{V MAX}}{I_{V MIN}} \leq 2$ .

See graph numbers 1, 2, 3D, 4B, 5B, 6D, 9, 11C on pages 25 - 27