


**FEATURES**

- Operates from a single +5V supply
- Differential PECL outputs
- Function and pinout compatible with Fairchild F100K
- Available in 24-pin CERPACK and 28-pin PLCC packages

**BLOCK DIAGRAM**





**DESCRIPTION**

The SY100S391 is a hex TTL-to-PECL translator for converting TTL logic levels to 100K logic levels. The unique feature of this translator is the ability to do this translation using only one +5V supply. The differential outputs allow each circuit to be used as an inverting/non-inverting translator, or as a differential line driver. A common enable (E), when LOW, holds all inverting outputs HIGH and all non-inverting inputs LOW.

The SY100S391 is ideal for those mixed PECL/TTL applications which only have a +5V supply available. When used in the differential mode, the S391, due to its high common mode rejection, overcomes voltage gradients between the TTL and PECL ground systems.

**PIN CONFIGURATIONS**



**PIN NAMES**

| Pin                       | Function                      |
|---------------------------|-------------------------------|
| D0 — D5                   | Data Inputs (TTL)             |
| Q0 — Q5                   | Data Outputs (PECL)           |
| $\bar{Q}_0$ — $\bar{Q}_5$ | Inverting Data Outputs (PECL) |
| E                         | Enable Input (TTL)            |
| VCCA                      | Vcco for ECL Outputs          |

**TRUTH TABLE**

| Inputs         |   | Outputs        |             |
|----------------|---|----------------|-------------|
| D <sub>n</sub> | E | Q <sub>n</sub> | $\bar{Q}_n$ |
| H              | H | H              | L           |
| L              | H | L              | H           |
| H              | L | L              | H           |
| L              | L | L              | H           |

**NOTE:**

1. H = High Voltage Level, L = Low Voltage Level


**GUARANTEED OPERATING CONDITIONS<sup>(1)</sup>**

| Symbol          | Rating                           | Value        | Unit |
|-----------------|----------------------------------|--------------|------|
| T <sub>A</sub>  | Operating Temperature Commercial | 0 to +85     | °C   |
| V <sub>CC</sub> | Supply Voltage                   | +4.5 to +5.5 | V    |

**NOTE:**

1. Do not exceed.

**LOGIC SYMBOL**



**ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>**

| Symbol             | Rating                                      | Value        | Unit |
|--------------------|---|--------------|------|
| —                  | TTL Input Voltage <sup>(2)</sup>            | -0.5 to +7.0 | V    |
| —                  | TTL Input Current <sup>(2)</sup>            | -30 to +5.0  | V    |
| —                  | PECL Output Current (DC Output HIGH)        | -50          | V    |
| —                  | V <sub>CC</sub> Pin Potential to Ground Pin | -0.5 to +7.0 | V    |
| T <sub>store</sub> | Storage Temperature                         | -65 to +150  | °C   |
| T <sub>J</sub>     | Max. Junction Temp.<br>Ceramic<br>Plastic   | +175<br>+150 | °C   |

**NOTES:**

- Permanent device damage may occur if ABSOLUTE MAXIMUM RATINGS are exceeded. This is a stress rating only and functional operation is not implied at conditions other than those detailed in the operational sections of this data sheet. Exposure to ABSOLUTE MAXIMUM RATING conditions for extended periods may affect device reliability.
- Either voltage limit or current limit is sufficient to protect inputs.

**TTL-TO-PECL DC ELECTRICAL CHARACTERISTICS<sup>(1)</sup>**

V<sub>CC</sub> = +5.0V ± 10%; GND = 0V

| Symbol           | Parameter                             | Min.                  | Typ.                  | Max.                  | Unit | Condition   |
|------------------|---------------------------------------|-----------------------|-----------------------|-----------------------|------|---|
| V <sub>OH</sub>  | Output HIGH Voltage                   | V <sub>CC</sub> -1025 | V <sub>CC</sub> -955  | V <sub>CC</sub> -870  | mV   | V <sub>IN</sub> = V <sub>IH</sub> (Max.) or V <sub>IL</sub> (Min.)  |
| V <sub>OL</sub>  | Output LOW Voltage                    | V <sub>CC</sub> -1890 | V <sub>CC</sub> -1705 | V <sub>CC</sub> -1620 |      | Loading with 50Ω to V <sub>CC</sub> -2V   |
| V <sub>OHc</sub> | Output HIGH Voltage Corner Point High | V <sub>CC</sub> -1035 | —                     | —                     | mV   | V <sub>IN</sub> = V <sub>IH</sub> (Min.) or V <sub>IL</sub> (Max.)<br>Loading with 50Ω to V <sub>CC</sub> -2V |
| V <sub>OLc</sub> | Output LOW Voltage Corner Point Low   | —                     | —                     | V <sub>CC</sub> -1610 | mV   |   |
| V <sub>IH</sub>  | Input HIGH Voltage                    | 2.0                   | —                     | 5.0                   | V    | Over V <sub>TTL</sub> , V <sub>EE</sub> , T <sub>A</sub> Range  |
| V <sub>IL</sub>  | Input LOW Voltage                     | 0                     | —                     | 0.8                   | V    | Over V <sub>TTL</sub> , V <sub>EE</sub> , T <sub>A</sub> Range  |
| I <sub>IH</sub>  | Input HIGH Current                    | —                     | —                     | 10                    | μA   | V <sub>IN</sub> = +2.7V   |
|                  | Breakdown Current                     | —                     | —                     | 100                   | μA   | V <sub>IN</sub> = +5.5V, V <sub>CC</sub> = Max.   |
| I <sub>IL</sub>  | Input LOW Current                     | D <sub>n</sub><br>E   | —                     | -0.8<br>-4.2          | mA   | V <sub>IN</sub> = +0.5V   |
| V <sub>CD</sub>  | Input Clamp Diode Voltage             | —                     | —                     | -1.2                  | V    | I <sub>IN</sub> = -18mA   |
| I <sub>CC</sub>  | V <sub>CC</sub> Supply Current        | 25                    | —                     | 69                    | mA   | Inputs Open   |

**NOTE:**

1. The specified limits represent the "worst case" value for the parameter. Since these values normally occur at the temperature extremes, additional noise immunity and guardbanding can be achieved by decreasing the allowable system operating ranges. Conditions for testing shown in the tables are chosen to guarantee operation under "worst case" conditions.


**AC ELECTRICAL CHARACTERISTICS**

**CERPACK AND PLCC**

VCC = +5.0V ± 10%


| Symbol       | Parameter                                      | TA = 0°C |      | TA = +25°C |      | TA = +85°C |      | Unit | Condition |
|--------------|--|----------|------|------------|------|------------|------|------|-----------|
|              |  | Min.     | Max. | Min.       | Max. | Min.       | Max. |      |           |
| tPLH<br>tPHL | Propagation Delay<br>Data and Enable to Output | 400      | 1400 | 400        | 1400 | 400        | 1400 | ps   |           |
| tTLH<br>tTHL | Transition Time<br>20% to 80%, 80% to 20%      | 350      | 1700 | 350        | 1700 | 350        | 1700 | ps   |           |

**TIMING DIAGRAM**



Propagation Delay and Transition Times


**TEST CIRCUIT**



**PRODUCT ORDERING CODE**

| Ordering Code | Package Type | Operating Range |
|---------------|--------------|-----------------|
| SY100S391FC   | F24-1        | Commercial      |
| SY100S391JC   | J28-1        | Commercial      |
| SY100S391JCTR | J28-1        | Commercial      |


**24 LEAD CERPACK (F24-1)**



- NOTES:**
1. DIMENSIONS ARE IN INCHES[MM].
  2. THIS DIMENSION INCLUDES GLASS PROTRUSION AND CAP TO BASE ALIGNMENT TOLERANCES.
  3. DIMENSIONS SHOWN ARE MAX/MIN, WHERE NOTED.

Rev.03

**28 LEAD PLCC (J28-1)**



- NOTES:**
1. DIMENSIONS ARE IN INCHES[MM].
  2. CONTROLLING DIMENSION: INCHES.
  3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.008[0.203].
  4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
  5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN
  6. PACKAGE TOP DIMENSION MAY BE SLIGHTLY SMALLER THAN BOTTOM DIMENSION.

Rev. 03

**MICREL-SYNERGY 3250 SCOTT BOULEVARD SANTA CLARA CA 95054 USA**

TEL + 1 (408) 980-9191 FAX + 1 (408) 914-7878 WEB <http://www.micrel.com>

This information is believed to be accurate and reliable, however no responsibility is assumed by Micrel for its use nor for any infringement of patents or other rights of third parties resulting from its use. No license is granted by implication or otherwise under any patent or patent right of Micrel Inc.

© 2000 Micrel Incorporated