

Table 1 For Data Terminal and Others (1) Dot type, Graphic type

Type No.	No. of Digits (Digits × lines)	Character Format, Symbol	Outline Dimensions							Fig. No.
			C.H (mm)	C.W (mm)	P.H (mm)	P.L (mm)	P.T (mm)	L.P (mm)	L.L (mm)	
FIP12XM2FA	12×2		11.3	7.25	63.0±1.0	164.0±1.0	12.3±0.7	2.54	8.0	D-4
FIP16X1KB	16×1		5.0	3.3	19.5±0.5	96.7±0.5	6.5±0.7	2.54	6.2	B-3
FIP16X1PA	16×1		5.0	3.3	20.0 ^{+1.0} _{-0.5}	98.0±1.0	6.5±0.7	1.5	5.0	A-3
FIP16XM1BB	16×1		11.3	7.25	35.0±1.0	208.0±1.0	8.0±0.7	2.54	14.0	C-4
FIP16XM1DB	16×1		11.25	7.2	36.0±1.0	202.5±1.0	9.0±0.7	2.54	14.0	C-4
FIP16XM2AB	16×2		11.3	7.25	51.0±1.0	208.0±1.0	10.3±0.7	2.54	14.0	D-4
FIP19X1AC	19×1		10.5	6.0	33.0±1.0	205.0±1.0	8.0±0.7	2.54	8.0	A-6
FIP20X1XA	20×1		5.0	3.5	28.0±1.0	138.0±0.7	8.0±0.7	2.54	14.0	D-4
FIP20X1DD	20×1		9.0	6.3	34.0±1.0	208.0±1.0	8.0±0.7	2.54	14.0	D-4
FIP20X1LD	20×1		5.05	3.3	20.5±1.0	115.7±1.0	6.5±0.7	2.54	6.2	B-5
FIP20X1TA	20×1		8.99	6.3	34.0±1.0	202.5±1.0	8.0±0.7	2.54	14.0	C-4
FIP20XM1BB	20×1		11.3	7.25	35.5±1.0	244.0±1.0	9.0±0.7	2.54	14.0	D-4
FIP20XM1CB	20×1		10.5	6.2	44.0±1.0	225.0±1.0	10.3±0.7	2.54	9.2	D-4
FIP20X2AC	20×2		5.05	3.55	35.0±1.0	125.0±1.0	7.8±0.7	2.54	14.0	D-4
FIP20X2EB	20×2		5.05	3.55	41.0±1.0	142.0±1.0	10.3±0.7	2.54	14.0	C-4
FIP20X2KB	20×2		9.5	6.2	40.0±1.0	185.0±1.0	10.2±0.7	2.0	4.7	D-2
FIP20X2LA	20×2		8.8	3.55	41.0±1.0	136.0±1.0	9.0±0.7	2.0	5.1	B-2
FIP20X2RA	20×2		11.3	7.25	53.0±1.0	250.0±1.0	10.3±0.7	2.54	16.5	C-4

Recommened Electrical Ratings											Note
Mode of Fil.	Ef (Vr.m.s.)	If (mAr.m.s.)	Mode of Ope.	$\frac{e_b = e_c}{V_{p-p}}$ * $\frac{E_b = E_c}{V_{dc}}$	Duty	Ek (Vdc)	ib/dig (mA)	ic/dig (mA)	(cd/m ²)	(fL)	
AC	6.2	260	dynamic	36.0	1/27	8.2	13.0	13.0	1000	(290)	
AC	3.9	84	dynamic	25.0	1/20	5.0	2.5	2.5	690	(200)	
AC	4.0	84	dynamic	35.0	1/17	5.8	4.0	4.0	1000	(290)	
AC	8.3	106	dynamic	35.0	1/20	7.0	20.0	20.0	1030	(300)	
AC	8.3	133	dynamic	43.0	1/38	8.0	26.0	23.0	1700	(500)	
AC	8.3	212	dynamic	43.0	1/20	10.0	30.0	25.0	1030	(300)	
AC	7.7	159	dynamic	50.0	1/23	10.0	9.0	14.0	690	(200)	
AC	5.5	84	dynamic	35.0	1/24	5.5	3.5	3.5	820	(240)	
AC	6.4	120	dynamic	35.0	1/24	8.5	9.0	9.0	1000	(290)	
AC	4.9	84	dynamic	27.0	1/25	6.0	2.7	2.9	680	(200)	
AC	6.4	120	dynamic	45.0	1/76.8	10.0	21.0	15.0	860	(250)	
AC	9.6	130	dynamic	45.0	1/25	10.0	20.0	25.0	1700	(500)	
AC	8.8	186	dynamic	35.0	1/24	10.0	13.5	14.0	860	(250)	
AC	6.0	125	dynamic	50.0	1/45	5.0	4.0	4.0	860	(250)	
AC	6.0	168	dynamic	35.0	1/24	7.0	6.0	10.0	700	(200)	
AC	6.6	200	dynamic	48.0	1/45	7.0	15.0	15.0	700	(200)	
AC	6.1	159	dynamic	45.0	1/45	8.2	8.5	15.0	700	(200)	
AC	9.5	212	dynamic	35.0	1/24	10.0	30.0	25.0	860	(250)	