

# Square Type

## 3.9 mm × 1.75 mm Series

Conventional Part No.	Global Part No.	Lighting Color
LN275RPX	LNG275RKR	Red
LN375GPX	LNG375GKG	Green
LN475YPX	LNG475YKX	Amber
LN875RPX	LNG875RKD	Orange

### Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ )

Lighting Color	$P_D$ (mW)	$I_F$ (mA)	$I_{FP}$ (mA)*	$V_R$ (V)	$T_{opr}$ ( $^\circ\text{C}$ )	$T_{stg}$ ( $^\circ\text{C}$ )
Red	70	25	150	4	-25 ~ +85	-30 ~ +100
Green	90	30	150	4	-25 ~ +85	-30 ~ +100
Amber	90	30	150	4	-25 ~ +85	-30 ~ +100
Orange	90	30	150	3	-25 ~ +85	-30 ~ +100

$I_{FP}$ の条件は  $\text{duty } 10\%$  Pulse width 1 msec. The condition of  $I_{FP}$  is duty 10%, Pulse width 1 msec

### Electro-Optical Characteristics ( $T_a = 25^\circ\text{C}$ )

Conventional Part No.	Lighting Color	Lens Color	$I_O$		$I_F$	$V_F$		$\lambda_P$	$\Delta\lambda$	$I_F$	$I_R$	
			Typ	Min		Typ	Max				Max	$V_R$
LN275RPX	Red	Red Diffused	0.5	0.2	15	2.2	2.8	700	100	20	5	4
LN375GPX	Green	Green Diffused	2.5	0.9	20	2.2	2.8	565	30	20	10	4
LN475YPX	Amber	Amber Diffused	2.0	0.7	20	2.2	2.8	590	30	20	10	4
LN875RPX	Orange	Red Diffused	3.0	1.0	20	2.1	2.8	630	40	20	10	3
Unit	—	—	mcd	mcd	mA	V	V	nm	nm	mA	$\mu\text{A}$	V

