

DN8648FBP


32-bit Shift Register Latch Driver IC

■ Overview

The DN8648FBP is an IC which incorporates a 32-bit shift register and a latch driver to meet high-speed operation low power consumption and high-density printout of the thermal printers for the work processors, and so on. It employs the Bi-CMOS process in which the serial-in and serial-out/parallel-out functions are incorporated, the 32-step shift register block and latch block are composed of CMOS, and the 32-step parallel driver block is bipolar.

■ Features


- Serial-in and serial-out/parallel-out
- Cascade connection allowed
- Built-in output malfunctioning preventive circuit
- Low current consumption at standby $I_{CC} \leq 100\mu A$
- High-breakdown, large current drive type output steps
Breakdown voltage : 30V
- Output current : 120mA (per pin)
- Surface mountable 44-pin flat package (pin pitch : 0.8mm)



■ Applications

- Driving of the thermal heads
- Driving of the relays, LEDs, solenoids, etc.

■ Block Diagram



■ Absolute Maximum Ratings (Ta = 25°C)

Parameter	Symbol	Rating	Unit
Supply voltage	V _{CC}	0 to 7	V
Output voltage	V _O	0 to 30	V
Output current	I _O	120 (Per one circuit)	mA
Power dissipation	P _D	1.8 *	W
Operating ambient temperature	T _{opr}	- 20 to + 75	°C
Storage temperature	T _{stg}	- 55 to + 125	°C

* When mounting onto the PCB, power dissipation is reduced at a rate of 15mW/°C from Ta= 25°C.

■ Recommended Operating Range (Ta=25°C)

Parameter	Symbol	Range
Operating supply voltage	V _{CC}	4 to 6V
Output voltage	V _O	below 30V
Output current	I _O	below 100mA *1
Clock frequency	f _{CLK}	below 10MHz *2
Input pulse width	CLK STB	t _w over 40ns over 40ns
Setup time	SIN STB	t _{su} over 30ns over 40ns
Hold time	SIN STB	t _h over 20ns over 0ns
Clock pulse rise time	t _r	below 500ns
Clock pulse fall time	t _f	below 500ns

*1 An allowable value changes depends on the number of simultaneously turned-on circuits and the duty. Use with power dissipation taken into full account.


*2 Input duty : 40 to 60%

■ Electrical Characteristics (Ta=25°C)

Parameter	Symbol	Condition	min	typ	max	Unit
Input voltage	V _{IH}	V _{CC} = 4 to 6V	0.7V _{CC}	—	V _{CC}	V
	V _{IL}		0	—	0.3V _{CC}	V
Input current	I _{IH}	V _{IH} = 5V	—	—	25	μA
	I _{IL}	V _{IL} = 0V	—	—	- 25	μA
Output voltage (SOUT)	V _{OH}	I _O = -1μA	4.9	—	—	V
	V _{OL}	I _O = 1μA	—	—	0.1	V
Output current (SOUT)	I _{OH}	V _{OH} = 4.5V	- 4	—	—	mA
	I _{OL}	V _{OL} = 0.4V	4	—	—	mA
Output saturation voltage (Q _n)	V _{CE(sat)1}	I _{OL} = 100mA	—	—	0.4	V
	V _{CE(sat)2}	I _{OL} = 80mA	—	—	0.35	V
Output leakage current	I _{OLK1}	V _O = 30V (output OFF)	—	—	50	μA
	I _{OLK2}	V _O = 15V (output OFF)	—	—	25	μA
Supply current	I _{CC1}	Total driver output OFF	—	—	100	μA
	I _{CC2}	Driver output 1 circuit ON	—	—	5	mA
Output malfunctioning preventive Circuit operating voltage	V _{CCT+}	*	2.9	—	3.9	V
	V _{CCT-}	*	2.6	—	3.6	V

* V_{CC}=5V unless otherwise specified

* Output malfunctioning preventive circuit operating voltage timing chart




■ Switching Characteristics (Ta = 25°C)

Parameter	Symbol	Input	Output	Condition	min	typ	max	Unit
Maximum clock frequency	$f_{max.}$	CLK			10	—	—	MHz
	t_{PLH}	CLK	SOUT	$V_{CC} = 5V$ $C_L = 15pF$	—	—	100	ns
	t_{PHL}				—	—	100	ns
Propagation delay time	t_{PLH}	CLK	\bar{Q}_n	$V_{CC} = 5V$ $R_L = 100\Omega$	—	—	2	μs
	t_{PHL}				—	—	0.5	μs
	t_{PLH}	EN	\bar{Q}_n	$C_L = 15pF$	—	—	2	μs
	t_{PHL}				—	—	0.5	μs


■ Supplementary Descriptions

- Timing Chart

1. Input Timing



2. Propagation Delay Time



■ Supplementary Descriptions (cont.)

- Function Table

Input				Driver output		SOUT
CLK	EN	STB	SIN	\bar{Q}_1	\bar{Q}_n	
\uparrow	L	\times	\times	H	H	Q'_{31}
\downarrow	L	\times	\times	H	H	nc
\uparrow	H	L	\times	nc	nc	Q'_{31}
\uparrow	H	H	L	H	\bar{Q}_{n-1}	Q'_{31}
\uparrow	H	H	H	L	\bar{Q}_{n-1}	Q'_{31}
\downarrow	H	H	\times	nc	nc	nc

Note) H = High level, L = Low level, \times = Either "H" or "L" will do, \uparrow = Transition from "H" to "L",

\downarrow = Transition from "H" to "L", nc = No change, Q'_{31} = Status of the 31st shift register

- Pin Assignments

