


HOLE LAYOUT  
(TOP VIEW)



SPECIFICATIONS:  
 RATING: 12V DC @ 1A  
 CONTACT RESISTANCE:  
 30 MOHMS MAX  
 INSULATION RESISTANCE:  
 100 MOHMS MIN @ 500V DC  
 WITHSTAND VOLTAGE:  
 500V AC FOR 1 MINUTE  
 LIFE: 5,000 CYCLES

NO.	DESCRIPTION	MATERIAL	QTY	FINISH
6	HOUSING	PBT	1	BLACK COLOR
5	BARREL	BRASS	1	NICKEL PLATED
4	TIP SPRING	0.25T TiCuR1-M-EH	1	SILVER PLATED
3	BREAK TERMINAL	0.3T BRASS	1	SILVER PLATED
2	RING SPRING	0.2T TiCuR1-M-EH	1	SILVER PLATED
1	EARTH TERMINAL	0.2T PHOSPHOR BRONZE	1	SILVER PLATED

**CUI INC**  
 9815 SW Allen, Suite 103  
 Beaverton, OR 97006  
 Phone: (503) 643-4899  
 800-276-4899  
 Fax: (503) 372-1266  
 Website: www.cui.com

TITLE:  
**3.5mm AUDIO JACK-STEREO**

PART NO.: SU-3524NG UNITS: MILLIMETERS

DRAWN BY: Todd R. White APPROVED BY: SCALE: 3X