

◆ FEATURE

- (1) 128*64 DOTS
- (2) 1/65 DUTY CYCLE
- (3) T.A.B. ASSEMBLY.

液晶之友 电话: 020-33819057
[Http://www.lcdfriends.com](http://www.lcdfriends.com)

◆ PIN TABLE

PIN NO.	SYMBOL	PIN NO.	SYMBOL
1	NC	24	CLS
2	TEMPS	25	MS
3	INTRS	26	DUTY1
4	HPM	27	DUTY0
5	DCDC5B	28	DB7(SID)
6	BSTS	29	DB6(SCLK)
7	V4	30	DB5
8	V3	31	DB4
9	V2	32	DB3
10	V1	33	DB2
11	V0	34	DB1
12	VR	35	DB0
13	C2-	36	E-RD
14	C2+	37	RW-WR
15	C1-	38	RS
16	C1+	39	RESETB
17	C3-	40	CS2
18	C3+	41	CS1B
19	VOUT	42	DISP
20	VDD	43	CL
21	VSS	44	M
22	PS	45	FRS
23	M1	46	NC

◆ ELECTRICAL CHARACTERISTICS

VSS=0V, AT 25°C

ITEMS	SYMBOL	MIN.	TYP.	MAX.	UNIT
SUPPLY VOLTAGE (LOGIC)	VDD	2.4	-	3.6	V
SUPPLY VOLTAGE (LCD)	V0	7.5	8.4	9.8	V
INPUT HIGH LEVEL VOLTAGE	VIH	0.8VDD	-	VDD	V
INPUT LOW LEVEL VOLTAGE	VIL	VSS	-	0.2VDD	V
OUTPUT HIGH LEVEL VOLTAGE	VOH	0.8VDD	-	VDD	V
OUTPUT LOW LEVEL VOLTAGE	VOL	VSS	-	0.2VDD	V
POWER SUPPLY CURRENT	IDD	-	-	-	mA

◆ BLOCK DIAGRAM

◆ OUTLINE DIMENSION

