


- NOTES:
1. DISPLAY TYPE
 2. VIEWING DIRECTION
 3. POLARIZER MODE
 4. DRIVE METHOD
 5. VEE
 6. VDD
 7. OPERATING TEMP.
 8. STORAGE TEMP.
 9. DRIVER
 10. BACKLIGHT
 11. BEZEL IS STAINLESS STEEL
 12. ALL UNMARKED TOLERANCES

COLOR STN
600
TRANSMISSIVE/NEGATIVE
1/240 DUTY 1/15 BIAS


CFFL(A/C/780V(TYP.), 5mA(TYP.) WHITE
LH156GF4
25°C~+55°C
-35°C~+65°C
5.0V
21.6V

DETAIL A:



CON 1		CON 2	
PIN	SYMBOL	PIN	SYMBOL
1	N	1	VFL1
2	VD	2	NC
3	LP	3	VFL2
4	XCK		
5	DISPDTF		
6	VDD		
7	VSS		
8	VEE		
9	D7		
10	D6		
11	D5		
12	D4		
13	D3		
14	D2		
15	D1		
16	D0		

COLOR FILTER



TIAN-MA MICROELECTRONICS CO.
2E/F, HANGOU Building, Shennan Road, Central, Shenzhen, China

DRAWN BY:	TTTTR: TM320240AKGV/T3	SCALE:	1:1
CHECKED BY:		UNIT:	mm
APPROVED BY:	DWG NO: G-1	SHEET NO: 1 OF 1	
CONFIRMED BY:	DWG NAME: TM320240AKGV/T3		

液晶之友 电话: 020-33819057
Http://www.lcdfriends.com