



**LK32A
THRU
LK34A**


3A SURFACE MOUNT SCHOTTKY BARRIER RECTIFIERS

FEATURES

- FOR SURFACE MOUNTED APPLICATIONS
- LOW PROFILE PACKAGE
- BUILT-IN STRAIN RELIEF
- EASY PICK AND PLACE
- PLASTIC MATERIAL USED CARRIES UNDERWRITERS LABORATORY CLASSIFICATION 94 V-0
- EXTREMELY LOW VF
- MAJORITY CARRIER CONDUCTION
- HIGH TEMPERATURE SOLDERING : 250°C/10 SECONDS AT TERMINALS

MECHANICAL DATA

- CASE : TSMA
- TERMINALS : SOLDER PLATED
- POLARITY : INDICATED BY CATHODE BAND
- WEIGHT : 0.10 GRAMS



CASE-TSMA

DIMENSIONS IN INCHES AND (MILLIMETERS)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

RATINGS AT 25°C AMBIENT TEMPERATURE UNLESS OTHERWISE SPECIFIED
SINGLE PHASE, HALF WAVE, 60 HZ, RESISTIVE OR INDUCTIVE LOAD.
FOR CAPACITIVE LOAD, DERATE CURRENT BY 20%

| RATINGS | SYMBOL | LK32A | LK34A | UNITS |
|--|-----------|--------------|-------|-------|
| MAXIMUM RECURRENT PEAK REVERSE VOLTAGE | V_{RRM} | 20 | 40 | V |
| MAXIMUM RMS VOLTAGE | V_{RMS} | 14 | 28 | V |
| MAXIMUM DC BLOCKING VOLTAGE | V_{DC} | 20 | 40 | V |
| MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT SEE FIG.1 | I_O | 3.0 | | A |
| MAXIMUM OVERLOAD SURGE 8.3ms SINGLE HALF SINE-WAVE | I_{FSM} | 80 | | A |
| STORAGE TEMPERATURE RANGE | T_{STG} | -55 TO + 150 | | °C |
| OPERATING TEMPERATURE RANGE | T_{OP} | -55 TO + 125 | | °C |

ELECTRICAL CHARACTERISTICS (At $T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

| CHARACTERISTICS | SYMBOL | LK32A | LK34A | UNITS |
|---|--------|-------|-------|-------|
| MAXIMUM FORWARD VOLTAGE AT 3.0A AC AND 25°C | V_F | 0.38 | 0.40 | V |
| MAXIMUM REVERSE CURRENT AT 25°C | I_R | 0.5 | | mA |

RATINGS AND CHARACTERISTIC CURVE LK32A THRU LK34A

FIG. 1 - FORWARD CURRENT DERATING CURVE




FIG. 2 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS




FIG. 5 - MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG. 4 - TYPICAL JUNCTION CAPACITANCE

