

DC/DC CONVERTER TRANSFORMERS

TYPE	DIMENSIONS (mm)	CONSTRUCTION	SPECIFICATIONS
EI-22 			Operating Freq. : Max. 300kHz Max. Operating Power : 7.8W (100kHz) 18.0W (300kHz)
EI-255B 			Operating Freq. : Max. 300kHz Max. Operating Power : 16.0W (100kHz) 38.0W (300kHz)
EI-28 			Operating Freq. : Max. 300kHz Max. Operating Power : 22.0W (100kHz) 51.0W (300kHz)
ERH2819 			Operating Freq. : Max. 500kHz Max. Operating Power : 10.0W (100kHz) 24.0W (300kHz) 36.0W (500kHz)
ERH2826 			Operating Freq. : Max. 500kHz Max. Operating Power : 11.0W (100kHz) 27.0W (300kHz) 40.0W (500kHz)
EI-30 			Operating Freq. : Max. 300kHz Max. Operating Power : 29.0W (100kHz) 67.0W (300kHz)
ER3023 			Operating Freq. : Max. 500kHz Max. operating power : 20W(500kHz) Weight : 30g
ER4831 			Inductance : Max. 56mH Operating Freq. : Max. 500kHz Max. operating power : 60W(500kHz) Weight : 75g

DC/DC CONVERTER TRANSFORMERS