


## 8 Channel, 140MHz Fully Integrated PDIC Receiver with 12 Gain settings

### FEATURES

- Data Channel Bandwidth: 140MHz
- Twelve Selectable Gain Settings
- > 60dB PSRR
- <10mV typical offset (Gains 1-32)
- 10ns Typical Setting Time
- -68dBm Noise Level (RF Channels)



### APPLICATIONS

- DVD-RW
- DVD-RAM
- CD/DVD COMBINATION DRIVES

### DESCRIPTION

The SP8055 is a PDIC specifically designed for high speed DVD-RW or DVD-RAM applications. The 8-channel wide-band design enables higher speed laser optic write operation in modern CD/DVD combination drives. Low noise operation allows data recovery (read) at very low signal levels. The SP8055 has 12 gain settings to allow maximum flexibility.

---

**ORDERING INFORMATION**

<b>Part Number</b>	<b>Temperature Range</b>	<b>Package Type</b>
SP8055 .....	-30°C to +80°C .....	16 Pin Chip-On-Board (COB)



ANALOG EXCELLENCE

**Sipex Corporation**

**Headquarters and  
Sales Office**

233 South Hillview Drive  
Milpitas, CA 95035  
TEL: (408) 934-7500  
FAX: (408) 935-7600

**Sales Office**

22 Linnell Circle  
Billerica, MA 01821  
TEL: (978) 667-8700  
FAX: (978) 670-9001  
e-mail: sales@sipex.com

Sipex Corporation reserves the right to make changes to any products described herein. Sipex does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights nor the rights of others.