

## 1 A POWER MINI MOLD TRIAC

## DESCRIPTION

The AC01DJM is all diffused type TRIAC granted RMS On-state Current 1 Amps, with rated voltages up to 400 volts.

This is designed specifically to be driven by low-level logic in any gating mode.

## FEATURES

- The AC01DJM offers sensitive gate specs of 5 and 10 mA, in all for quadrants.
- You can fill the gap between microprocessor controls and the power-output requirements.
- This is housed in the popular SOT-89 package.
- The package features excellent environmental stress and temperature cycling.

## QUALITY GRADE

Standard


Please refer to "Quality grade on NEC Semiconductor Devices" (Document number IEI-1209) published by NEC Corporation to know the specification of quality grade on the devices and its recommended applications.

## APPLICATIONS

Solid-state relays, microprocessor interfacing, TTL logic and various solid-state switch designs alone or with larger TRIAC.

ABSOLUTE MAXIMUM RATINGS ( $T_a = 25\text{ }^\circ\text{C}$ )

CHARACTERISTIC	SYMBOL	MAXIMUM RATINGS	UNIT	NOTE
Repetitive Peak Off Voltage	$V_{DRM}$	400	V	
Non-repetitive Peak Off Voltage	$V_{DSM}$	500	V	
RMS On-State Current	$I_{T(RMS)}$	1 ( $T_c = 113\text{ }^\circ\text{C}$ )	A	See Fig. 12
Peak Surge On-State Current	$I_{TSM}$	7 (50 Hz), 8 (60 Hz)	A	See Fig. 2
Fusing Current	$\int i^2 dt$	0.2 ( $1\text{ ms} \leq t \leq 10\text{ ms}$ )	$\text{A}^2\text{s}$	
Peak Gate Power Dissipation	$P_{GM}$	1 ( $f \geq 50\text{ Hz}$ , Duty $\leq 10\%$ )	W	
Average Gate Power Dissipation	$P_{G(AV)}$	0.1	W	
Peak Gate Current	$I_{GM}$	$\pm 0.5$ ( $f \geq 50\text{ Hz}$ , Duty $\leq 10\%$ )	A	
Junction Temperature	$T_j$	125	$^\circ\text{C}$	
Storage Temperature	$T_{stg}$	-55 to +150	$^\circ\text{C}$	

PACKAGE DIMENSIONS  
(in millimeters)

## Pin Connections

1.  $T_1$  Terminal
2.  $T_2$  Terminal
3. Gate

\* Measure point of Case Temperature

**ELECTRICAL CHARACTERISTICS (T<sub>a</sub> = 25 °C)**

CHARACTERISTIC		SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT	NOTE	
Peak Off-State Current		I <sub>DRM</sub>	V <sub>DM</sub> = V <sub>DRM</sub>	T <sub>j</sub> = 25 °C	-	-	10	μA	
				T <sub>j</sub> = 125 °C	-	-	100		
On-State Voltage		V <sub>TM</sub>	I <sub>TM</sub> = 1.2 A	-	-	1.5	V	See Fig. 1	
DC Gate Trigger Current	MODE I	I <sub>GT</sub>	V <sub>DM</sub> = 12 V R <sub>L</sub> = 100 Ω	G; Positive, T <sub>2</sub> ; Positive	-	-	5	mA	See Fig. 5, 7
	II			G; Negative, T <sub>2</sub> ; Positive	-	-	10		
	III			G; Negative, T <sub>2</sub> ; Negative	-	-	5		
	IV			G; Positive, T <sub>2</sub> ; Negative	-	-	5		
DC Gate Trigger Voltage	MODE I	V <sub>GT</sub>	V <sub>DM</sub> = 12 V R <sub>L</sub> = 100 Ω	G; Positive, T <sub>2</sub> ; Positive	-	-	1.0	V	See Fig. 6, 8
	II			G; Negative, T <sub>2</sub> ; Positive	-	-	1.5		
	III			G; Negative, T <sub>2</sub> ; Negative	-	-	1.0		
	IV			G; Positive, T <sub>2</sub> ; Negative	-	-	1.0		
Gate Non-Trigger Voltage		V <sub>GD</sub>	T <sub>j</sub> = 125 °C, V <sub>DM</sub> = 1/2 V <sub>DRM</sub>	0.1	-	-	V		
DC Holding Current		I <sub>H</sub>	V <sub>D</sub> = 24 V, I <sub>TM</sub> = 1 A	-	-	10	mA		
Critical Rate of Rise of Off-State Voltage		dv/dt	T <sub>j</sub> = 125 °C, V <sub>DM</sub> = 2/3 V <sub>DRM</sub> Gate Open Circuited Exponential Waveform	-	10	-	V/μs		
Critical Rate of Rise of Commutating Off-State Voltage		(dv/dt) <sub>c</sub>	T <sub>j</sub> = 125 °C, I <sub>TM</sub> = 1.2 A (di <sub>T</sub> /dt) <sub>c</sub> = -0.5 A/ms V <sub>DM</sub> = 400 V	0.5	-	-	V/μs		
Steady State		R <sub>th(j-c)</sub>	Junction to Case	-	-	10	°C/W	See Fig. 13	
Thermal Resistance		R <sub>th(j-a)</sub>	Junction to Ambient	-	-	120	°C/W		

**TYPICAL CHARACTERISTICS (T<sub>a</sub> = 25 °C)**





Fig. 3  $V_G - I_G$  RATING




Fig. 4 GATE CHARACTERISTIC




Fig. 5 GATE CHARACTERISTIC




Fig. 6  $I_{GT} - T_a$  TYPICAL DISTRIBUTION




Fig. 7  $V_{GT} - T_a$  TYPICAL DISTRIBUTION




Fig. 8  $i_{GT} - \tau$  TYPICAL DISTRIBUTION




Fig. 9  $v_{GT} - \tau$  TYPICAL DISTRIBUTION




Fig. 10  $I_H - T_a$  TYPICAL DISTRIBUTION




Fig. 11  $P_{T(AV)} - I_{T(RMS)}$  CHARACTERISTIC




Fig. 12  $T_c - I_{T(RMS)}$  RATING




Fig. 13  $T_a - I_{T(RMS)}$  RATING





Fig. 14  $Z_{th}$  CHARACTERISTIC



REFERENCE

Document name	Document No.
Quality control guide of semiconductor devices	MEI-1202
Assembly manual of semiconductor devices	IEI-1207

[MEMO]

No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Corporation. NEC Corporation assumes no responsibility for any errors which may appear in this document.

NEC Corporation does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from use of a device described herein or any other liability arising from use of such device. No license, either express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Corporation or others.

The devices listed in this document are not suitable for use in aerospace equipment, submarine cables, nuclear reactor control systems and life support systems. If customers intend to use NEC devices for above applications or they intend to use "Standard" quality grade NEC devices for applications not intended by NEC, please contact our sales people in advance.

Application examples recommended by NEC Corporation.

Standard: Computer, Office equipment, Communication equipment, Test and Measurement equipment, Machine tools, Industrial robots, Audio and Visual equipment, Other consumer products, etc.

Special: Automotive and Transportation equipment, Traffic control systems, Antidisaster systems, Anticrime systems, etc.

This datasheet has been download from:

[www.datasheetcatalog.com](http://www.datasheetcatalog.com)

Datasheets for electronics components.