



CX24113 Features

- RF input: 925–2175 MHz
- Input power range: -20 to -90 dBm
- Symbol rate: 1–45 MSps
- Noise figure: 10 dB, typical
- Input IP3 at minimum gain: 10 dBm, typical
- Baseband filter bandwidth: 3–40 MHz
- Output voltage: 0.5 Vp-p @ RL > 1 k Ω
- Operating temperature: 0–85° C
- Package type: 36-pin, Pb-free, QFN

Applications

- DSS/DVB set-top boxes
- Digital VCR (DVR)
- Commercial digital video, audio, and data receivers

© 2004, Conexant Systems, Inc. All Rights Reserved. Conexant and the Conexant logo are trademarks of Conexant Systems, Inc. All other trademarks are owned by their respective owners. Although Conexant strives for accuracy in all its publications, this material may contain errors or omissions and is subject to change without notice. **THIS MATERIAL IS PROVIDED AS IS AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.** Conexant shall not be liable for any special, indirect, incidental or consequential damages as a result of its use.

www.conexant.com
General Information:
U.S. and Canada: (888) 855-4562
International: (732) 345-7500
Headquarters
100 Schultz Drive
Red Bank, NJ 07701
Order# 102435B

