

MA3D798

Silicon epitaxial planar type (cathode common)

For switching power supply


■ Features

- TO-220D package
- Allowing to rectify under ($I_{F(AV)} = 20$ A) condition
- Cathode common dual type
- Low V_F (forward voltage) type: $V_F < 0.47$ V (at $I_F = 10$ A)

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Repetitive peak reverse voltage	V_{RRM}	30	V
Average forward current	$I_{F(AV)}$	20	A
Non-repetitive peak forward surge current*	I_{FSM}	120	A
Junction temperature	T_j	-40 to +125	°C
Storage temperature	T_{stg}	-40 to +125	°C

Note) * : Half sine-wave; 10 ms/cycle



■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reverse current (DC)	I_R	$V_R = 30$ V			5	mA
Forward voltage (DC)	V_F	$I_F = 10$ A			0.47	V
High voltage rectification	$R_{th(j-c)}$	Direct current (between junction and case)			3	°C/W

Note) Rated input/output frequency: 150 MHz

