


### FRED Diode

- Fast recovery epitaxial diode
- Soft recovery characteristics



| Type    | $V_{RRM}$ | $I_{FRMS}$ | $t_{rr}$ | Package   | Ordering Code   |
|---------|-----------|------------|----------|-----------|-----------------|
| BYP 101 | 1000V     | 25A        | 80ns     | TO-218 AD | C67047-A2072-A2 |

### Maximum Ratings

| Parameter  | Symbol        | Values        | Unit             |
|--|---------------|---------------|------------------|
| Mean forward current<br>$T_C = 90\text{ °C}, D = 0.5$                                      | $I_{FAV}$     | 15            | A                |
| RMS forward current  | $I_{FRMS}$    | 25            |                  |
| Surge forward current, sine halfwave, aperiodic<br>$T_j = 100\text{ °C}, f = 50\text{ Hz}$ | $I_{FSM}$     | 70            |                  |
| Repetitive peak forward current<br>$T_j = 100\text{ °C}, t_p \leq 10\text{ }\mu\text{s}$   | $I_{FRM}$     | 150           | A <sup>2</sup> s |
| $i^2t$ value<br>$T_j = 100\text{ °C}, t_p = 10\text{ ms}$                                  | $\int I^2 dt$ | 25            |                  |
| Repetitive peak reverse voltage  | $V_{RRM}$     | 1000          | V                |
| Surge peak reverse voltage   | $V_{RSM}$     | 1000          |                  |
| Power dissipation<br>$T_C = 90\text{ °C}$  | $P_{tot}$     | 40            | W                |
| Chip or operating temperature  | $T_j$         | -40 ... + 150 | °C               |
| Storage temperature  | $T_{stg}$     | -40 ... + 150 |                  |
| Thermal resistance, chip case  | $R_{thJC}$    | $\leq 1.5$    | K/W              |
| Thermal resistance, chip-ambient   | $R_{thJA}$    | $\leq 46$     |                  |
| DIN humidity category, DIN 40 040  | -             | E             | -                |
| IEC climatic category, DIN IEC 68-1  | -             | 40 / 150 / 56 | -                |

## Electrical Characteristics, at $T_j = 25\text{ °C}$ , unless otherwise specified

| Parameter | Symbol | Values |      |      | Unit |
|-----------|--------|--------|------|------|------|
|           |        | min.   | typ. | max. |      |

### Static Characteristics

|   |       |   |                      |                |    |
|---|-------|---|----------------------|----------------|----|
| Forward voltage drop<br>$I_F = 15\text{ A}$ , $T_j = 25\text{ °C}$<br>$I_F = 15\text{ A}$ , $T_j = 100\text{ °C}$   | $V_F$ | - | 2<br>1.7             | 2.4<br>-       | V  |
| Reverse current<br>$V_R = 1000\text{ V}$ , $T_j = 25\text{ °C}$<br>$V_R = 1000\text{ V}$ , $T_j = 100\text{ °C}$<br>$V_R = 1000\text{ V}$ , $T_j = 150\text{ °C}$ | $I_R$ | - | 0.01<br>0.05<br>0.15 | 0.25<br>-<br>- | mA |


### AC Characteristics

|  |           |   |     |   |               |
|--|-----------|---|-----|---|---------------|
| Reverse recovery charge<br>$I_F = 15\text{ A}$ , $V_{CC} = 300\text{ V}$ , $dI_F/dt = -1000\text{ A}/\mu\text{s}$<br>$T_j = 100\text{ °C}$       | $Q_{rr}$  | - | 2.2 | - | $\mu\text{C}$ |
| Peak reverse recovery current<br>$I_F = 15\text{ A}$ , $V_{CC} = 300\text{ V}$ , $dI_F/dt = -1000\text{ A}/\mu\text{s}$<br>$T_j = 100\text{ °C}$ | $I_{RRM}$ | - | 35  | - | A             |
| Reverse recovery time<br>$I_F = 15\text{ A}$ , $V_{CC} = 300\text{ V}$ , $dI_F/dt = -1000\text{ A}/\mu\text{s}$<br>$T_j = 100\text{ °C}$         | $t_{rr}$  | - | 80  | - | ns            |
| Storage time<br>$I_F = 15\text{ A}$ , $V_{CC} = 300\text{ V}$ , $dI_F/dt = -1000\text{ A}/\mu\text{s}$<br>$T_j = 100\text{ °C}$                  | $t_S$     | - | 45  | - |               |
| Softfaktor<br>$I_F = 15\text{ A}$ , $V_{CC} = 300\text{ V}$ , $dI_F/dt = -1000\text{ A}/\mu\text{s}$<br>$T_j = 100\text{ °C}$                    | S         | - | 0.8 | - | -             |

### Typ. forward characteristics

$$I_F = f(V_F)$$


parameter:  $T_j$



### Typ. reverse current

$$I_{RRM} = f(dI_F / dt)$$

parameter:  $V_{CC} = 300\text{ V}, I_F = 15\text{ A}, T_j = 100^\circ\text{C}$



### Typ. reverse recovery charge

$$Q_{rr} = f(dI_F / dt)$$

parameter:  $V_{CC} = 300\text{ V}, I_F = 15\text{ A}, T_j = 100^\circ\text{C}$

