

Silicon RECTIFIER


A500

3000 Volts 740 Amps Avg.

The A500 Series of high power rectifier diodes feature the newly developed, multi-diffused technology in a new General Electric pressure-mounted package.

FEATURES:

- High Current, *High Voltage*
- Pressure Contacts
- Glazed Ceramic Package with 1" Creepage Path
- Reversibility (eliminates need for special reverse polarity units)
- Hermetic Seal
- Available in Factory Assembled Heat Exchangers or Ready-to-Mount



IMPORTANT: Mounting instructions on the last page of the C501 specification must be followed.

MAXIMUM ALLOWABLE RATINGS

| TYPE | REPETITIVE PEAK REVERSE VOLTAGE, V_{RRM} $T_J = -40^{\circ}\text{C to } +175^{\circ}\text{C}$ | NON-REPETITIVE REVERSE VOLTAGE, V_{RSM} $T_J = 0^{\circ}\text{C to } +175^{\circ}\text{C}$ | V_{RRM}/V_{RSM} $T_J = -40^{\circ}\text{C to } +200^{\circ}\text{C}$ |
|--------|--|---|---|
| A500LP | 3000 Volts | 3100 Volts | 2600 Volts |
| A500LT | 2900 | 3000 | 2500 |
| A500LN | 2800 | 2900 | 2400 |
| A500LS | 2700 | 2800 | 2300 |
| A500LM | 2600 | 2700 | 2200 |
| A500LE | 2500 | 2600 | 2100 |
| A500LD | 2400 | 2500 | 2000 |
| A500LC | 2300 | 2400 | 1900 |
| A500LB | 2200 | 2300 | 1800 |
| A500LA | 2100 | 2200 | 1700 |
| A500L | 2000 | 2100 | 1600 |
| A500PT | 1900 | 2000 | 1500 |
| A500PN | 1800 | 1900 | 1400 |
| A500PS | 1700 | 1800 | 1300 |
| A500PM | 1600 | 1700 | 1200 |

| | |
|--|---|
| Average Forward Current | 740 Amperes, 1 Φ Average |
| Peak One-Cycle Surge Current | 10,000 Amperes |
| Minimum I^2t Rating (for times ≥ 1.5 msec) | 363,000 Ampere ² Seconds |
| Minimum I^2t Rating (at 8.3 msec) | 415,000 Ampere ² Seconds |
| Maximum Forward Voltage Drop ($T_C = 150^{\circ}\text{C}$, 1000 Amps. Peak) | 1.26 Volts |
| Peak Reverse Leakage Current ($T_J = 175^{\circ}\text{C}$, $V = \text{Rated } V_{RRM}$) | 35mA |
| Maximum Thermal Resistance, $R_{\theta JS}$ (1 ϕ) (Double-Side Cooling) | 0.06 $^{\circ}\text{C/Watt}$ |
| Storage Temperature, T_{STG} | -40 $^{\circ}\text{C to } +200^{\circ}\text{C}$ |
| Operating Temperature, T_J | 0 $^{\circ}\text{C to } +175^{\circ}\text{C}$ |
| Mounting Force Required | 2200 Lbs. \pm 10% 9.8 KN \pm 10% |


NOTES:

¹ Assumes a heatsink thermal resistance of less than 1.1 $^{\circ}\text{C/watt}$.


² Non-recurrent voltage and current ratings, as contrasted to repetitive ratings which apply for occasional or unpredictable overloads. For example, the forward surge current ratings are non-recurrent ratings that are used in fault coordination work.

607 A-----00500-1X


A500




1. AVERAGE FORWARD CURRENT VERSUS MAXIMUM ALLOWABLE SINK TEMPERATURE



2. AVERAGE FORWARD POWER DISSIPATION VERSUS AVERAGE FORWARD CURRENT




3. MAXIMUM HEAT EXCHANGER TEMPERATURE VERSUS AVERAGE FORWARD CURRENT FOR DOUBLE-SIDE COOLING




4. TRANSIENT THERMAL IMPEDANCE - JUNCTION-TO-CASE

NOTES:


1. Power "D" adds .01°C/W to account for both case to dissipator interfaces, when properly mounted; e.g., $R_{\theta JS} = .06°C/W$. See Mounting Instructions.
2. DC Thermal Impedance is based on average full cycle junction temperature. Instantaneous junction temperature may be calculated using the following modifications.
 - end of conducting portion of cycle
 - 120° sq. wave add .0065°C/W along entire curve
 - 180° sq. wave add .0047°C/W along entire curve
 - 180° sine wave add .0026°C/W along entire curve
 - end of full cycle
 - any wave, subtract .0026°C/W along entire curve




5. REVERSE RECOVERY CHARACTERISTICS



6. MAXIMUM SURGE CURRENT FOLLOWING RATED LOAD CONDITIONS




7. SUBCYCLE PEAK SURGE FORWARD CURRENT AND I^2t RATING FOLLOWING RATED LOAD CONDITIONS



8. MAXIMUM ON-STATE CHARACTERISTICS

OUTLINE DRAWING



NOTE:
1. GLAZED CERAMIC INSULATOR
WITH 1.00 INCH MIN. SURFACE
CREEPPAGE (25.40mm)

| SYMBOL | INCHES | | MILLIMETERS | | NOTE |
|----------|--------|-------|-------------|-------|------|
| | MIN | MAX | MIN | MAX | |
| ϕA | — | 2.000 | — | 50.80 | |
| ϕB | 1.240 | 1.260 | 31.50 | 32.00 | |
| C | 1.000 | 1.060 | 25.40 | 26.92 | |
| D | .080 | — | 2.03 | — | |
| ϕE | 0.136 | 0.146 | 3.45 | 3.71 | |
| F | .034 | — | 0.86 | — | |
| G | — | — | — | — | 1 |

A-----00500-3A