




## Power Transformers Fully Enclosed 4801 - 4807

LOW VOLTAGE RECTIFIER Transformers with fully enclosed vertical end covers.

- Primary voltage, 115 Volts, 60 Hz.
- Primary and secondary leads 8-10" long.
- 4-hole vertical mounting.
- 7 sizes are available, covering the range: 30 to 100 VA.
- CSA listed (LR 47366).



### MECHANICAL



Dimensions, Inches

P/N	DIMENSIONS				D	E	F	G
	L	W	H					
4801	2.50	2.13	3.00	2.00	1.19	0.375	0.190	
4802	2.50	2.38	3.00	2.00	1.44	0.375	0.190	
4803	2.50	2.63	3.00	2.00	1.68	0.375	0.190	
4804	2.50	2.88	3.00	2.00	1.94	0.375	0.190	
4805	2.50	3.13	3.00	2.00	2.19	0.375	0.190	
4806	2.50	3.38	3.00	2.00	2.44	0.375	0.190	
4807	2.50	3.63	3.00	2.00	2.69	0.375	0.190	

### ELECTRICAL SPECIFICATION

Part No.	F.L. Volts	Secondary Voltages (A-A)		Current Amps
		N.L. Volts		
4801-01	5.0	5.40		3.00
4802-01	5.0	5.43		6.00
4802-02	6.3	6.90		4.00
4802-03	12.6	13.80		2.00
4802-04	25.0	27.50		1.00
4802-05	28.0	30.80		1.00
4802-06	36.0	39.50		1.00
4802-07	50.0	51.80		5.00
4802-08	60.0	65.20		0.50
4803-01	5.0	5.35		8.00
4803-02	6.3	6.70		6.00
4803-03	10.0	10.70		4.00
4803-04	16.0	17.40		3.00
4803-05	18.0	19.40		3.00
4803-06	25.0	26.80		1.50
4803-07	33.0	35.00		1.00
4803-08	50.0	54.50		1.00
4803-09	80.0	85.50		0.50
4803-10	100.0	107.00		0.50
4804-01	5.0	5.35	10.00	
4804-02	6.3	6.74	8.00	
4804-03	10.0	10.70	5.00	
4804-04	10.0	10.70	5.00	
4804-05	11.0	11.80	5.00	
4804-06	12.6	13.40	4.00	
4804-07	14.0	15.10	4.00	

Part No.	F.L. Volts	Secondary Voltages (A-A)		Current Amps
		N.L. Volts		
4804-08	24.0	25.60		2.00
4804-09	28.0	29.80		2.00
4804-10	30.0	31.60		1.50
4805-01	6.3	6.70	10.00	
4805-02	20.0	20.80	3.00	
4805-03	36.0	38.30	2.00	
4805-04	60.0	63.50	1.00	
4805-05	120.0	127.00	0.50	
4806-01	5.0	5.30	15.00	
4806-02	6.3	6.80	12.00	
4806-03	10.0	10.60	8.00	
4806-04	12.6	13.60	6.00	
4806-05	25.0	26.80	3.00	
4806-06	28.0	29.60	3.00	
4807-01	5.0	5.30	20.00	
4807-02	10.0	10.70	10.00	
4807-03	12.6	13.30	8.00	
4807-04	14.0	15.10	6.00	
4807-05	16.0	17.40	5.00	
4807-06	18.0	18.70	5.00	
4807-07	25.0	26.60	4.00	
4807-08	30.0	32.00	3.00	
4807-09	44.0	46.00	2.00	
4807-10	50.0	53.20	2.00	
4807-11	80.0	85.20	0.50	
4807-12	100.0	106.50	1.00	