



DTC144E**NPN SILICON TRANSISTOR****NPN DIGITAL TRANSISTOR
(BUILT-IN BIAS RESISTORS)****■ FEATURES**

- * Built-in bias resistors that implies easy ON/OFF applications.
- * The bias resistors are thin-film resistors with complete isolation to allow negative input.


■ EQUIVALENT CIRCUIT

*Pb-free plating product number:DTC144EL

■ ORDERING INFORMATION

Order Number		Package	Pin Assignment			Packing
Normal	Lead Free Plating		1	2	3	
DTC144E-AE3-R	DTC144EL-AE3-R	SOT-23	G	I	O	Tape Reel
DTC144E-AL3-R	DTC144EL-AL3-R	SOT-323	G	I	O	Tape Reel
DTC144E-AN3-R	DTC144EL-AN3-R	SOT-523	G	I	O	Tape Reel
DTC144E-T9S-R	DTC144EL-T9S-R	TO-92SP	G	O	I	Tape Reel

	(1) R: Tape Reel (2) AE3: SOT-23, AL3: SOT-323, AN3: SOT-523 (3) L: Lead Free Plating, Blank: Pb/Sn
--	---

■ MARKING(For SOT Package)

DTC144E

NPN EPITAXIAL SILICON TRANSISTOR

■ ABSOLUTE MAXIMUM RATINGS (Ta = 25 °C)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V _{CC}	50	V
Input Voltage	V _{IN}	-10 ~ +12	V
Output Current	I _{OUT}	100	mA
	I _{OUT(MAX)}	100	mA
	P _C	300	mW
Power Dissipation	TO-92SP	150	mW
	SOT-523	200	mW
	SOT-23/SOT-323	+150	
Junction Temperature	T _J	+150	
Storage Temperature	T _{STG}	-55~+150	





Note Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS (Ta = 25 °C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Input Voltage	V _{IN(OFF)}	V _{CC} = 5V, I _{OUT} =100 μA			0.5	V
	V _{IN(ON)}	V _{OUT} = 0.3V, I _{OUT} = 20mA	3			
Output Voltage	V _{OUT(ON)}	I _{OUT} /I _{IN} = 10mA / 0.5 mA			0.3	V
Input Current	I _{IN}	V _{IN} = 5V			0.18	mA
Output Current	I _{OUT(OFF)}	V _{CC} = 50V , V _{IN} =0V			0.5	μA
DC Current Gain	h _{FE}	V _{OUT} = 5V, I _{OUT} = 5mA	68			
Input Resistance	R ₁		32.9	47	61.1	k
Resistance Ratio	R ₂ /R ₁		0.8	1	1.2	
Transition Frequency	f _T	V _{CE} = 10 V, I _E = -5mA, f=100MHz		250		MHz

TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.