

IF1331

N-Channel Silicon Junction Field-Effect Transistor

• Low-Noise, High Gain Amplifier

Absolute maximum ratings at $T_A = 25^\circ\text{C}$

Reverse Gate Source & Reverse Gate Drain Voltage	- 20 V
Continuous Forward Gate Current	10 mA
Continuous Device Power Dissipation	225 mW
Power Derating	1.8 mW/ $^\circ\text{C}$
Storage Temperature Range	- 65 $^\circ\text{C}$ to 200 $^\circ\text{C}$

At 25°C free air temperature:

Static Electrical Characteristics

		IF1331		Process NJ132H	
		Min	Max	Unit	Test Conditions
Gate Source Breakdown Voltage	$V_{(\text{BR})\text{GSS}}$	- 20		V	$I_G = - 1 \mu\text{A}$, $V_{DS} = \emptyset\text{V}$
Gate Reverse Current	I_{GSS}		- 0.1	nA	$V_{DS} = \emptyset\text{V}$, $V_{GS} = - 10\text{V}$
Gate Source Cutoff Voltage	$V_{GS(\text{OFF})}$	- 0.35	- 1.5	V	$V_{DS} = 10\text{V}$, $I_D = 0.5 \text{nA}$
Drain Saturation Current (Pulsed)	I_{DSS}	5	20	mA	$V_{DS} = 10\text{V}$, $V_{GS} = \emptyset\text{V}$

Dynamic Electrical Characteristics

Common Source Forward Transconductance	g_{fs}	10		mS	$V_{DS} = 10\text{V}$, $I_D = 5 \text{mA}$	$f = 1 \text{ kHz}$
Common Source Input Capacitance	C_{iss}		20	pF	$V_{DS} = 10\text{V}$, $I_D = 5 \text{mA}$	$f = 1 \text{ MHz}$
Common Source Reverse Transfer Capacitance	C_{rss}		5	pF	$V_{DS} = 10\text{V}$, $I_D = 5 \text{mA}$	$f = 1 \text{ MHz}$

Typ

Equivalent Short Circuit Input Noise Voltage	\bar{e}_N		2.5	nV/ $\sqrt{\text{Hz}}$	$V_{DS} = 10\text{V}$, $I_D = 5 \text{mA}$	$f = 1 \text{ kHz}$
--	-------------	--	-----	------------------------	---	---------------------

TO-72 Package
Dimensions in Inches (mm)

Pin Configuration
1 Source, 2 Drain, 3 Gate, 4 Case