


IGBT MODULE

1200V / 15A / PIM



■ Features

- High Speed Switching
- Voltage Drive
- Low Inductance Module Structure
- Converter Diode Bridge Dynamic Brake Circuit

■ Applications

- Inverter for Motoe Drive
- AC and DC Servo Drive Amplifier
- Uninterruptible Power Supply

■ Maximum ratings and characteristics

● Absolute maximum ratings (Tc=25°C unless without specified)

Item	Symbol	Condition	Rating	Unit	
Inverter	Collector-Emitter voltage	V _{CES}	1200	V	
	Gate-Emitter voltage	V _{GES}	±20	V	
	Collector current	I _C	Continuous	15	A
		I _{CP}	1ms	30	A
		-I _C		15	A
	Collector power dissipation	P _C	1 device	120	W
Brake	Collector-Emitter voltage	V _{CES}	1200	V	
	Gate-Emitter voltage	V _{GES}	±20	V	
	Collector current	I _C	Continuous	10	A
		I _{CP}	1ms	20	A
	Collector power dissipation	P _C	1 device	88	W
	Repetitive peak reverse voltage	V _{RRM}		1200	V
	Average forward current	I _{F(AV)}		1	A
Surge current	I _{FSM}	10ms	50	A	
Converter	Repetitive peak reverse voltage	V _{RRM}		1600	V
	Non-Repetitive peak reverse voltage	V _{RSM}		1700	V
	Average output current	I _O	50Hz/60Hz sine wave	25	A
	Surge current (Non-Repetitive)	I _{FSM}	T _j =150°C, 10ms	320	A
	I ² _t (Non-Repetitive)		T _j =150°C, 10ms	512	A²s
Operating junction temperature		T _j		+150	°C
Storage temperature		T _{stg}		-40 to +125	°C
Isolation voltage		V _{iso}	AC : 1 minute	AC 2500	V
Mounting screw torque				1.7 * ₁	N·m

*₁ Recommendable value : 1.3 to 1.7 N·m (M4)

● Electrical characteristics (Tj=25°C unless without specified)


Item	Symbol	Condition	Characteristics			Unit
			Min.	Typ.	Max.	
Inverter (IGBT)	Zero gate voltage collector current	ICES	VCE=1200V, VGE=0V			1.0
	Gate-Emitter leakage current	IGES	VCE=0V, VGE=±20V			20
	Gate-Emitter threshold voltage	VGE(th)	VCE=20V, Ic=15mA			4.5
	Collector-Emitter saturation voltage	VCE(sat)	VGE=15V, Ic=15A			3.3
	Collector-Emitter voltage	-VCE	-Ic=15A			3.0
	Input capacitance	Cies	VGE=0V, VCE=10V, f=1MHz			2400
	Switching time	ton	VCC=600V			1.2
		tr	Ic=15A			0.6
		toff	VGE=±15V			1.5
		tf	RG=82 ohm			0.5
	Reverse recovery time of FRD	trr	IF=15A			0.35
Brake (IGBT)	Zero gate voltage collector current	ICES	VCE=1200V, VGE=0V			1.0
	Gate-Emitter leakage current	IGES	VCE=0V, VGE=±20V			0.1
	Collector-Emitter saturation voltage	VCE(sat)	Ic=10A, VGE=15V			3.3
	Switching time	ton	VCC=600V			0.8
		tr	Ic=10A			0.6
		toff	VGE=±15V			1.5
		tf	RG=120 ohm			0.5
Brake (FWD)	Reverse current	IRRM	VR=1200V			1
	Reverse recovery time	trr				0.6
Converter	Forward voltage	VFM	IF=25A			1.4
	Reverse current	IRRM	VR=1600V			1.0

● Thermal Characteristics

Item	Symbol	Condition	Characteristics			Unit
			Min.	Typ.	Max.	
Thermal resistance (1 device)	Rth(j-c)	Inverter IGBT			1.04	°C/W
		Inverter FRD			2.78	
		Brake IGBT			1.43	
		Converter Diode			3.40	
Contact thermal resistance *	Rth(c-f)	With thermal compound		0.05		







* This is the value which is defined mounting on the additional cooling fin with thermal compound







■ Equivalent Circuit Schematic






■ Characteristics (Representative)







● Inverter









● Brake




Switching time vs. R_G
 $V_{CC}=600V$, $I_C=10A$, $V_{GE}=\pm 15V$, $T_J=25^\circ C$




Dynamic input characteristics
 $T_J=25^\circ C$




Reversed biased safe operating area
 $+V_{GE}=15V$, $-V_{GE} \leq 15V$, $T_J \leq 125^\circ C$, $R_G \geq 120 \text{ ohm}$



Switching loss vs. Collector current
 $V_{CC}=600V$, $R_G=120 \text{ ohm}$, $V_{GE}=\pm 15V$



Capacitance vs. Collector-Emmitter voltage
 $T_J=25^\circ C$



■ Outline Drawings, mm

