

POWER SCHOTTKY RECTIFIER

MAIN PRODUCT CHARACTERISTICS

$I_{F(AV)}$	1 A
V_{RRM}	150 V
$T_j (max)$	175°C
$V_F (max)$	0.67 V

FEATURES AND BENEFITS

- NEGLIGIBLE SWITCHING LOSSES
- LOW FORWARD VOLTAGE DROP FOR HIGHER EFFICIENCY AND EXTENDED BATTERY LIFE
- LOW THERMAL RESISTANCE
- AVALANCHE CAPABILITY SPECIFIED


DESCRIPTION

150V Power Schottky rectifier are suited for switch Mode Power Supplies on up to 24V rails and high frequency converters.

Packaged in SMA and Axial, this device is intended for use in consumer & computer applications like TV, STB, PC and DVD where low drop forward voltage is required to reduce power dissipation.



DO-41
STPS1150



SMA
STPS1150A

ABSOLUTE RATINGS (limiting values)

Symbol	Parameter			Value	Unit
V _{RRM}	Repetitive peak reverse voltage			150	V
I _{F(RMS)}	RMS forward current			15	A
I _{F(AV)}	Average forward current	T _L = 160°C δ = 0.5	SMA	1	A
		T _L = 150°C δ = 0.5	DO-41		
I _{FSM}	Surge non repetitive forward current	Half wave, single phase, 50Hz	SMA	50	A
			DO-41	75	
P _{ARM}	Repetitive peak avalanche power	tp = 1μs Tj = 25°C		1500	W
T _{stg}	Storage temperature range			- 65 to + 150	°C
T _j	Maximum junction temperature *			175	°C
dV/dt	Critical rate of rise of reverse voltage (rated V _R , T _j = 25°C)			10000	V/μs

* : $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th(j-a)}}$ thermal runaway condition for a diode on its own heatsink

THERMAL RESISTANCES

Symbol	Parameter			Value	Unit
$R_{th(j-l)}$	Junction to leads	Lead length = 10 mm	DO-41	30	$^{\circ}\text{C/W}$
			SMA	20	

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Tests conditions		Min.	Typ.	Max.	Unit
I_R^*	Reverse leakage current	$T_j = 25^{\circ}\text{C}$	$V_R = 150\text{V}$		0.2	1	μA
		$T_j = 125^{\circ}\text{C}$			0.2	1	mA
V_F^*	Forward voltage drop	$T_j = 25^{\circ}\text{C}$	$I_F = 1\text{A}$		0.78	0.82	V
		$T_j = 125^{\circ}\text{C}$			0.62	0.67	
		$T_j = 25^{\circ}\text{C}$	$I_F = 2\text{A}$		0.85	0.89	
		$T_j = 125^{\circ}\text{C}$			0.69	0.75	

Pulse test : * $t_p \leq 250\text{ }\mu\text{s}$, $\delta < 2\%$

To evaluate the maximum conduction losses use the following equation:

$$P = 0.59 \times I_{F(AV)} + 0.08 \times I_{F(RMS)}^2$$

Fig. 1: Conduction losses versus average current.




Fig. 3: Normalized avalanche power derating versus pulse duration.




Fig. 2: Average forward current versus ambient temperature ($\delta = 0.5$).




Fig. 4: Normalized avalanche power derating versus junction temperature.




Fig. 5-1: Non repetitive surge peak forward current versus overload duration (maximum values) (SMA).




Fig. 5-2: Non repetitive surge peak forward current versus overload duration (maximum values) (DO-41).




Fig. 6-1: Relative variation of thermal impedance junction to ambient versus pulse duration (SMA).




Fig. 6-2: Relative variation of thermal impedance junction to ambient versus pulse duration (DO-41).




Fig. 7: Reverse leakage current versus reverse voltage applied (typical values).




Fig. 8: Junction capacitance versus reverse voltage applied (typical values).




Fig. 9-1: Forward voltage drop versus forward current (low level).




Fig. 9-2: Forward voltage drop versus forward current (high level).




Fig. 10: Thermal resistance junction to ambient versus copper surface under each lead (Epoxy printed circuit board FR4, Cu: 35μm) (SMA).






Fig. 11: Thermal resistance versus lead length (DO-15).




PACKAGE MECHANICAL DATA
DO-41 plastic



PACKAGE MECHANICAL DATA
SMA (JEDEC DO-214AC)

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.70	0.075	0.106
A2	0.05	0.20	0.002	0.008
b	1.25	1.65	0.049	0.065
c	0.15	0.41	0.006	0.016
E	4.80	5.60	0.189	0.220
E1	3.95	4.60	0.156	0.181
D	2.25	2.95	0.089	0.116
L	0.75	1.60	0.030	0.063

FOOT PRINT DIMENSIONS (in millimeters)


Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STPS1150	STPS1150	DO-41	0.34 g	2000	Ammopack
STPS1150RL	STPS1150	DO-41	0.34 g	5000	Tape & Reel
STPS1150A	1150	SMA	0.068 g	5000	Tape & Reel

- Epoxy meets UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2003 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany
 Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore
 Spain - Sweden - Switzerland - United Kingdom - United States.

<http://www.st.com>

