

MNLM131-X REV 0BL

 Original Creation Date: 07/07/95
 Last Update Date: 10/23/97
 Last Major Revision Date: 07/07/95

PRECISION VOLTAGE-TO-FREQUENCY CONVERTERS

Industry Part Number

LM131

NS Part Numbers

LM131H/883

Prime Die

LM131

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883, Method 5005

Subgrp	Description	Temp (°C)
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

Electrical Characteristics

DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: $4V \leq V_{CC} \leq 40V$

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
Vio	Input Comparator Offset Voltage	Vcc = 5V			-10	10	mV	1, 2, 3
Iio	Input Comparator Offset Current	Vcc = 5V			-100	100	nA	1
					-150	150	nA	2, 3
Iib	Input Comparator Bias Current	Vcc = 5V			-300		nA	1
					-500		nA	2, 3
Vcm	Common Mode Voltage Range		4		-.2	Vcc-2	V	1, 2, 3
Vth	Timer Threshold Voltage, Pin 5		4		63	70	% of Vcc	1
Iib	Timer Input Bias Current, Pin 5	Vcc = 5V, Vpin 5 ≤ 3V			-.1	.1	uA	1
		Vcc = 5V, Vpin 5 ≤ 3V			-.2	.2	uA	2, 3
		Vcc = 5V, Vpin 5 ≤ 3.7V				.5	uA	1
		Vcc = 5V, Vpin 5 ≤ 3.7V				2	uA	2, 3
Vsat	Pin 5 Saturation Voltage	Vcc = 5V, Ipin 5 = 5mA				.5	V	1, 2, 3
Iout	Output Current, Pin 1	Vcc = 5V, Vpin 1=0V, Rs=13.6K Ohms			-144	-126	uA	1
					-146	-126	uA	2, 3
		Vcc = 40V, Vpin 1=0V, Rs=13.6K Ohms			-144	-126	uA	1
					-146	-126	uA	2, 3
Delta Iout	Output Current Change	Vcc = 40V				1	uA	1
						1.5	uA	2, 3
Ioff	Off State Output Leakage	Vcc = 5V			-6	6	nA	1
					-50	50	nA	2, 3
		Vcc = 40V			-6	6	nA	1
					-50	50	nA	2, 3
Vref	Reference Voltage, Pin 2	Vcc = 5V			1.76	2.02	V	1, 2, 3
		Vcc = 40V			1.76	2.02	V	1, 2, 3
Vsat	Frequency Output Saturation Voltage	Vcc = 5V, Ipin 3 = 5mA				.5	V	1, 2, 3
		Ipin 3 = 3.2mA	4			.4	V	1, 2, 3

Electrical Characteristics

DC PARAMETERS(Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: $4V \leq V_{CC} \leq 40V$

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
I _{off}	Off State Output Leakage, Pin 3	V _{CC} = 5V				1	uA	1
						1.2	uA	2, 3
		V _{CC} = 40V				1	uA	1
						1.2	uA	2, 3
I _{CC}	Power Supply Current	V _{CC} = 5V			2	4	mA	1
					1.8	5.2	mA	2, 3
		V _{CC} = 40V			2.5	6	mA	1
					1.5	7	mA	2, 3

AC PARAMETERS

	VFC Non-Linearity	V _{CC} = 15V, $5.5V \leq V_{in} \leq 11V$	2, 3, 5		-.01	.01	% FS	4
		V _{CC} = 15V, $5.5V \leq V_{in} \leq 11V$	2, 3, 5		-.02	.02	% FS	5, 6
A _v	Conversion Accuracy Scale Factor	V _{CC} = 15V, V _{in} =-10V, R _s =14K Ohms	5		.95	1.05	KHz/V	4
			5		.945	1.055	KHz/V	5, 6
T _c A _v	Temperature Stability of Gain	V _{CC} = 15V, V _{in} =-10V, R _s =14K Ohms	5		-150	150	ppm/C	4, 5, 6
Delta A _v	Change of Gain with V _{CC}	$15V \leq V_{CC} \leq 20V$	5		-.06	.06	%/V	4
P _f s	Rated Full Scale Frequency	V _{CC} = 15V, V _{in} = -10V	1, 5		10		KHz	4
Delta P _f s	Overrange Frequency	V _{CC} = 15V, V _{in} = -11V	1, 5		10		%	4

Note 1: Parameter tested go-no-go only.

Note 2: Tested at 25 C, guaranteed but not tested at +125C and -55C.

Note 3: Non-linearity is defined as the deviation of f_{OUT} from V_{in} X (10KHz/-10Vdc) when the circuit has been trimmed for zero error at 10Hz and 10KHz, over the frequency range 1Hz to 11KHz. For the timing capacitor (CT) use NOP ceramic, Teflon TM or Polystyrene TM.

Note 4: Guaranteed parameter, not tested.

Note 5: Bench tested per RPI-3-295.

Revision History

Rev	ECN #	Rel Date	Originator	Changes
0BL	M0002521	10/23/97	Barbara Lopez	Update MDS: MNLM131-X Rev. 0AL to MNLM131-X rev. 0BL for Lifetime Buy.