



ELECTRONICS, INC.  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089  
<http://www.nteinc.com>

## NTE30005, NTE30006, NTE30007 Light Emitting Diode (LED) 0603 Surface Mount

**Description:**

The NTE30005 thru NTE30007 are 1.6mm x 0.8mm chip LED lamps in a 0603 surface mount type package. The High Efficiency Red source color device (NTE30005) is made with Gallium Arsenide Phosphide on Gallium Phosphide Orange Light Emitting Diode. The Super Bright Green source color device (NTE30006) is made with Gallium Phosphide Green Light Emitting Diode. The Yellow source color device (NTE30007) is made with Gallium Arsenide Phosphide on Gallium Phosphide Yellow Light Emitting Diode.

**Features:**

- 1.6mm x 0.8mm (0603) SMT LED, 0.75mm Thickness
- Low Power Consumption
- Wide Viewing Angle
- Ideal for Backlight and Indicator Applications

**Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

DC Forward Current, $I_F$		
NTE30005, NTE30007	30mA	
NTE30006	25mA	
Peak Forward Current (Note 1), $I_{F(\text{peak})}$		
NTE30005	160mA	
NTE30006, NTE30007	140mA	
Reverse Voltage, $V_R$	5V	
Viewing Angle ( $2\theta_{1/2}$ )	120°	
Power Dissipation, $P_D$	105mW	
Operating Temperature Range, $T_{opr}$	-40° to +85°C	
Storage Temperature Range, $T_{stg}$	-40° to +85°C	

Note 1. 1/10 Duty Cycle, 0.1ms Pulse Width.

Note 2.  $\theta_{1/2}$  is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.

**Electrical/Optical Characteristics:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Luminous Intensity	$I_v$	$I_F = 20\text{mA}$				
NTE30005			5	12	-	mcd
NTE30006			3	10	-	mcd
NTE30007			3	8	-	mcd

**Electrical/Optical Characteristics (Cont'd):** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage NTE30005	$V_F$	$I_F = 20\text{mA}$	-	2.0	2.5	V
NTE30006			-	2.2	2.5	V
NTE30007			-	2.1	2.5	V
Reverse Current	$I_R$	$V_R = 5\text{V}$	-	-	10	$\mu\text{A}$
Peak Emission Wave Length NTE30005	$\lambda_P$	$I_F = 20\text{mA}$	-	627	-	nm
NTE30006			-	565	-	nm
NTE30007			-	590	-	nm
Dominate Wavelength NTE30005	$\lambda_D$	$I_F = 20\text{mA}$	-	625	-	nm
NTE30006			-	568	-	nm
NTE30007			-	588	-	nm
Spectral Line Half Width NTE30005	$\Delta\lambda$	$I_F = 20\text{mA}$	-	45	-	nm
NTE30006			-	30	-	nm
NTE30007			-	25	-	nm
Capacitance NTE30005, NTE30006	C	$V_F = 0\text{V}, f = 1\text{MHz}$	-	15	-	pF
NTE30007			-	20	-	pF

