

TOSHIBA GTR MODULE SILICON N CHANNEL IGBT


M G 100 J 7 K S 50

HIGH POWER SWITCHING APPLICATIONS

Unit in mm


MOTOR CONTROL APPLICATIONS

- The Electrodes are isolated from Case.
- High Input Impedance
- 7 IGBTs Built into 1 Package.
- Enhancement-Mode
- High Speed Type IGBT
 - : $V_{CE(sat)} = 2.5 \text{ V (Max.) (@} I_C = 100 \text{ A)}$
 - : $t_f = 0.5 \mu\text{s (Max.) (@} I_C = 100 \text{ A)}$
 - : $t_{rr} = 0.3 \mu\text{s (Max.) (@} I_F = 100 \text{ A)}$



Weight : 520 g (Typ.)

EQUIVALENT CIRCUIT



Signal Terminal

1 : G (U)	2 : Open	3 : E (U)	4 : G (V)
5 : Open	6 : E (V)	7 : G (W)	8 : Open
9 : E (W)	10 : G (B)	11 : G (X)	12 : G (Y)
13 : G (Z)	14 : Open	15 : Open	16 : E

961001EAA1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

INVERTER STAGE

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Emitter Voltage		V _{CES}	600	V
Gate-Emitter Voltage		V _{GES}	±20	V
Collector Current	DC	I _C	100	A
	1 ms	I _{CP}	200	
Forward Current	DC	I _F	100	A
	1 ms	I _{FM}	200	
Collector Power Dissipation (T _c = 25°C)		P _C	300	W
Junction Temperature		T _j	150	°C
Storage Temperature Range		T _{stg}	−40~125	°C
Isolation Voltage		V _{Isol}	2500 (AC 1 min.)	V
Screw Torque (Terminal / Mounting)		—	3 / 3	N·m

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Gate Leakage Current		I _{GES}	V _{GE} = ±20 V, V _{CE} = 0 V	—	—	±500	nA
Collector Cut-Off Current		I _{CES}	V _{CE} = 600 V, V _{GE} = 0 V	—	—	1.0	mA
Gate-Emitter Cut-Off Voltage		V _{GE (off)}	V _{CE} = 5 V, I _C = 10 mA	5.0	—	8.0	V
Collector-Emitter Saturation Voltage		V _{CE (sat)}	I _C = 100 A, V _{GE} = 15 V	—	2.0	2.5	V
Input Capacitance		C _{ies}	V _{CE} = 10 V, V _{GE} = 0 V, f = 1 MHz	—	8.5	—	nF
Forward Voltage		V _F	I _F = 100 A	—	2.3	3.0	V
Switching Time	Rise Time	t _r	Inductive-Load V _{CC} = 300 V I _C = 100 A V _{GE} = ±15 V R _G = 13 Ω (Note 1)	—	0.12	0.24	μs
	Turn-On Time	t _{on}		—	0.45	0.90	
	Fall Time	t _f		—	0.20	0.50	
	Turn-Off Time	t _{off}		—	0.50	1.00	
	Reverse Recovery Time	t _{rr}		—	0.10	0.30	
Thermal Resistance		R _{th (j-c)}	Transistor Stage	—	—	0.42	°C / W
			Diode Stage	—	—	1.00	
		R _{th (c-f)}	Case to fin (Note 2)	—	0.05	—	

(Note 2) : Silicone Grease is applied.

BRAKE STAGE

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Emitter Voltage		V _{CES}	600	V
Gate-Emitter Voltage		V _{GES}	±20	V
Collector Current	DC	I _C	50	A
	1 ms	I _{CP}	100	
Forward Current	DC	I _F	50	A
	1 ms	I _{FM}	100	
Collector Power Dissipation (T _c = 25°C)		P _C	80	W
Junction Temperature		T _j	150	°C
Storage Temperature Range		T _{stg}	−40~125	°C
Isolation Voltage		V _{Isol}	2500 (AC 1 min.)	V
Screw Torque (Terminal / Mounting)		—	3 / 3	N·m

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Gate Leakage Current		I _{GES}	V _{GE} = ±20 V, V _{CE} = 0 V	—	—	±500	nA
Collector Cut-Off Current		I _{CES}	V _{CE} = 600 V, V _{GE} = 0 V	—	—	1.0	mA
Gate-Emitter Cut-Off Voltage		V _{GE (off)}	V _{CE} = 5 V, I _C = 5 mA	5.0	—	8.0	V
Collector-Emitter Saturation Voltage		V _{CE (sat)}	I _C = 50 A, V _{GE} = 15 V	—	2.0	2.5	V
Input Capacitance		C _{ies}	V _{CE} = 10 V, V _{GE} = 0 V, f = 1 MHz	—	4.0	—	nF
Forward Voltage		V _F	I _F = 50 A	—	2.2	2.8	V
Switching Time	Rise Time	t _r	Inductive-Load V _{CC} = 300 V I _C = 50 A V _{GE} = ±15 V R _G = 24 Ω (Note 1)	—	0.08	0.16	μs
	Turn-On Time	t _{on}		—	0.10	0.20	
	Fall Time	t _f		—	0.22	0.44	
	Turn-Off Time	t _{off}		—	0.50	1.00	
	Reverse Recovery Time	t _{rr}		—	0.23	0.35	
Thermal Resistance		R _{th (j-c)}	Transistor Stage	—	—	1.56	°C / W
			Diode Stage	—	—	2.00	
		R _{th (c-f)}	Case to fin (Note 2)	—	0.05	—	

(Note 2) : Silicone Grease is applied.

(Note 1) : Switching Time Test Circuit & Timing Chart

