

DIODE ARRAY PRODUCT SPECIFICATION

MONOLITHIC AIR ISOLATED DIODE ARRAY

FEATURES:

- HERMETIC CERAMIC PACKAGE
- $V_b > 60V$ at 10uA
- $I_r < 100nA$ at 40V
- $C < 4.0$ pF

Absolute Maximum Ratings:

Symbol	Parameter	Limit	Unit
VBR(R)	*1 *2 Reverse Breakdown Voltage	60	Vdc
IO	*1 *3 Continuous Forward Current	300	mAdc
IFSM	*1 Peak Surge Current (tp= 1/120 s)	500	mAdc
PT1	*4 Power Dissipation per Junction @ 25°C	400	mW
PT2	*4 Power Dissipation per Package @ 25°C	500	mW
Top	Operating Junction Temperature Range	-65 to +150	°C
Tstg	Storage Temperature Range	-65 to +200	°C



NOTE 1: Each Diode

NOTE 2: Pulsed: PW = 100ms max.; duty cycle \leq 20%

NOTE 3: Derate at 2.4mA/°C above +25 °C

NOTE 4: Derate at 4.0mW/°C above +25 °C

Electrical Characteristics (Per Diode) @ 25°C unless otherwise specified



PACKAGE OUTLINE

Symbol	Parameter	Conditions	Min	Max	Unit
Vf1	Forward Voltage	If = 100mAdc *1		1	Vdc
Vf2	Forward Voltage	If = 500mAdc *1		1.5	Vdc
IR1	Reverse Current	VR = 40 Vdc	0.1		uAdc
Ct	Capacitance (pin to pin)	VR = 0 Vdc ; f = 1 MHz		4.0	pF
tfr	Forward Recovery Time	If = 500mAdc		40	ns
trr	Reverse Recovery Time	If = IR = 200mAdc, irr = 20mAdc, RL = 100 ohms		20	ns

NOTE 1: Pulsed: PW = 300us +/- 50us, duty cycle \leq 2%, 90us after leading edge

Sertech reserves the right to make changes to any product design, specification or other information at any time without prior notice.