

## 2SK3679-01MR (900V/1.58Ω/9A)

1) Package TO-220F

## 2) Absolute Maximum Ratings (Tc=25 unless otherwise specified)

Items	Symbols	Ratings	Units
Drain-Source Voltage	$V_{DS}$	900	V
Continuous Drain Current	$I_D$	±9	A
Pulsed Drain Current	$I_{D(pulse)}$	±36	A
Gate-Source Voltage	$V_{GS}$	±30	V
Repetitive and Non-Repetitive Maximum Avalanche Current	$I_{AR}$	9	A
Non-Repetitive Maximum Avalanche Energy	$E_{AS}$	287.7	mJ *1
Maximum Drain-Source dV/dt	dV <sub>DS</sub> /dt	20	kV/us
Peak Diode recovery dV/dt	dV/dt	5	kV/us *2
Maximum Power Dissipation	$P_D @ T_c=25$	95	W
	$P_D @ T_a=25$	2.16	W
Operating and Storage	$T_{ch}$	150	
Temperature range	$T_{stg}$	-55 ~ +150	

## 3)Electrical Characteristics (Tch=25 unless otherwise specified)

Items	Symbols	Test Conditions	min.	typ.	max.	Units
Drain-Source Breakdown Voltage	$BV_{DSS}$	$I_D=250\mu A$ $V_{GS}=0V$	900	---	---	V
Gate Threshold Voltage	$V_{GS(th)}$	$I_D=250\mu A$ $V_{DS}=V_{GS}$	3.0	---	5.0	V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=900V$ $T_{ch}=25$	---	---	25	$\mu A$
		$V_{GS}=0V$ $T_{ch}=125$	---	---	250	$\mu A$
Gate-Source Leakage Current	$I_{GSS}$	$V_{GS}=\pm 30V$ $V_{DS}=0V$	---	---	100	nA
Drain-Source On-State Resistance	$R_{DS(on)}$	$I_D=4.5A$ $V_{GS}=10V$	---	---	1.58	
Input Capacitance	$C_{iss}$	$V_{DS}=25V$	---	1200	---	pF
Output Capacitance	$C_{oss}$	$V_{GS}=0V$	---	140	---	
Reverse Transfer Capacitance	$C_{rss}$	$f=1MHz$	---	7	---	nC
Total Gate Charge	$Q_g$	$V_{cc}=450V$	---	32	---	
Gate to Source Charge	$Q_{gs}$	$I_D=9A$	---	7	---	
Gate to Drain (Miller) Charge	$Q_{gd}$	$V_{GS}=10V$	---	7	---	
Avalanche Capability	$I_{AV}$	$L=6.51mH$ $T_{ch}=25$	12	---	---	A
Diode Forward On-Voltage	$V_{SD}$	$I_F=9A, V_{GS}=0V, T_{ch}=25$	---	1.0	1.5	V

## 4) Thermal Characteristics

Items	Symbols	Test Conditions	min.	typ.	max.	Units
Channel to Case	$R_{th(ch-c)}$				1.316	/W
Channel to Ambient	$R_{th(ch-a)}$				58.0	/W

\*1 L=6.51mH, Vcc=90V

\*2  $I_F \leq -I_D$ ,  $-di/dt=50A/\mu s$ ,  $V_{cc} \leq BV_{DSS}$ ,  $T_{ch} \leq 150^\circ C$ 

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

	DATE	NAME	APPROVED	Fuji Electric Co.,Ltd.	
DRAWN	Sep. -10-'02	T. Kuboyama	T. HOSEN	MT5F12613	1 / 1
CHECKED	Sep. -10-'02	T. Yamada			
REVISIONS					