







★ MAXIMUM RATINGS

Parameter	Symbol	5P4SMA	5P6SMA	Unit	Remarks
Non-repetitive Peak Reverse Voltage	V_{RSM}	500	700	V	–
Non-repetitive Peak Off-state Voltage	V_{DSM}	500	700	V	–
Repetitive Peak Reverse Voltage	V_{RRM}	400	600	V	–
Repetitive Peak Off-state Voltage	V_{DRM}	400	600	V	–
Average On-state Current	$I_{T(AV)}$	5 ($T_C = 94^\circ\text{C}$, single phase half wave, $\theta = 180^\circ$)		A	Refer to Figure 11 .
Effective On-state Current	$I_{T(RMS)}$	8		A	
Surge On-state Current	I_{TSM}	80 (50 Hz, sine half wave, 1 cycle) 88 (60 Hz, sine half wave, 1 cycle)		A	Refer to Figure 2 .
Fusing Current	$\int i_t^2 dt$	28 (1 ms $\leq t \leq$ 10 ms)		A ² s	–
Critical Rate Rise of On-state Current	di/dt	50		A/ μs	–
Peak Gate Power Dissipation	P_{GM}	5 ($f \geq 50$ Hz, Duty $\leq 10\%$)		W	Refer to Figure 3 .
Average Gate Power Dissipation	$P_{G(AV)}$	0.5		W	
Peak Gate Forward Current	I_{FGM}	2 ($f \geq 50$ Hz, Duty $\leq 10\%$)		A	–
Peak Gate Reverse Voltage	V_{RGM}	10		V	–
Junction Temperature	T_j	–40~+125		$^\circ\text{C}$	–
Storage Temperature	T_{stg}	–55~+150		$^\circ\text{C}$	–

★ ELECTRICAL CHARACTERISTICS ($T_j = 25^\circ\text{C}$)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit	Remarks	
Repetitive Peak Reverse Current	I_{RRM}	$V_{RM} = V_{RRM}$	$T_j = 25^\circ\text{C}$	–	–	100	μA	–
			$T_j = 125^\circ\text{C}$	–	–	2	mA	–
Repetitive Peak Off-state Current	I_{DRM}	$V_{DM} = V_{DRM}$	$T_j = 25^\circ\text{C}$	–	–	100	μA	–
			$T_j = 125^\circ\text{C}$	–	–	2	mA	–
On-state Voltage	V_{TM}	$I_{TM} = 10$ A	–	–	1.4	V	Refer to Figure 1 .	
Gate Trigger Current	I_{GT}	$V_{DM} = 6$ V, $R_L = 100$ Ω	–	–	10	mA	Refer to Figure 4 .	
Gate Trigger Voltage	V_{GT}	$V_{DM} = 6$ V, $R_L = 100$ Ω	–	–	1.5	V		
Gate Non-trigger Voltage	V_{GD}	$T_j = 125^\circ\text{C}$, $V_{DM} = \frac{1}{2} V_{DRM}$	0.2	–	–	V	–	
Holding Current	I_H	$V_{DM} = 24$ V, $I_{TM} = 10$ A	–	6	–	mA	–	
Critical Rate Rise of Off-state Voltage	dv/dt	$T_j = 125^\circ\text{C}$, $V_{DM} = \frac{2}{3} V_{DRM}$	–	40	–	V/ μs	–	
Circuit Commuted Turn-off Time	t_q	$T_j = 125^\circ\text{C}$, $I_{TM} = 5$ A, $di/dt = 15$ A/ μs , $V_R \geq 25$ V, $V_{DM} = \frac{2}{3} V_{DRM}$, $dV_D/dt = 10$ V/ μs	–	50	–	μs	–	
Thermal Resistance ^{Note}	$R_{th(j-c)}$	Junction to case DC	–	–	4.2	$^\circ\text{C/W}$	Refer to Figure 13 .	
	$R_{th(j-a)}$	Junction to ambient DC	–	–	60	$^\circ\text{C/W}$		

★ TYPICAL CHARACTERISTICS












Figure 13. Z_{th} CHARACTERISTIC



- **The information in this document is current as of June, 2004. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC Electronics data sheets or data books, etc., for the most up-to-date specifications of NEC Electronics products. Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.**

- No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Electronics. NEC Electronics assumes no responsibility for any errors that may appear in this document.
- NEC Electronics does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC Electronics products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Electronics or others.
- Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of a customer's equipment shall be done under the full responsibility of the customer. NEC Electronics assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
- While NEC Electronics endeavors to enhance the quality, reliability and safety of NEC Electronics products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC Electronics products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment and anti-failure features.
- NEC Electronics products are classified into the following three quality grades: "Standard", "Special" and "Specific".

The "Specific" quality grade applies only to NEC Electronics products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of an NEC Electronics product depend on its quality grade, as indicated below. Customers must check the quality grade of each NEC Electronics product before using it in a particular application.

"Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots.

"Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support).

"Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.

The quality grade of NEC Electronics products is "Standard" unless otherwise expressly specified in NEC Electronics data sheets or data books, etc. If customers wish to use NEC Electronics products in applications not intended by NEC Electronics, they must contact an NEC Electronics sales representative in advance to determine NEC Electronics' willingness to support a given application.

(Note)

- (1) "NEC Electronics" as used in this statement means NEC Electronics Corporation and also includes its majority-owned subsidiaries.
- (2) "NEC Electronics products" means any product developed or manufactured by or for NEC Electronics (as defined above).