

5.0Vdc HCMOS/TTL COMPATIBLE SMD CRYSTAL CLOCK OSCILLATOR



7.0 x 5.0 x 1.8mm

ASLV SERIES

* RoHS COMPLIANT

FEATURES:

- Low profile (1.7) ceramic VCXO
- Enable/Disable functions
- 7.0mm x 5.0mm seam welded
- HCMOS/TTL output
- Suitable for reflow methods

APPLICATIONS:

- Phase locked loops (PLLs)
- Synthesizers
- Clock Recover, Digital Transmission device
- Digital set-top box

STANDARD SPECIFICATIONS:

PARAMETERS	
Frequency Range	1.00 MHz to 155.52 MHz
Operating Temperature	0°C to + 70°C
Storage Temperature	- 55°C to + 125°C
Overall Frequency Stability	± 50 ppm max.
Supply Voltage (Vdd)	5.0 Vdc ± 5%
Input Current	30mA max.
Symmetry	40/60 % max. @ 1/2Vdd (see options)
Rise and Fall Time (Tr/Tf)	8nS max
Output Load	15pF (2TTL)
Output Disable/Enable time	100ns max
Output Voltage	VOH = 0.9*Vdd min VOL = 0.4 Vdc max
Pulling	± 100 ppm min.
Start-up Time	10mS max
Tristate Function	"1" (VIH >= 2.2 Vdc) or open: Oscillation "0" (VIL < 0.8 Vdc) : Option A/Hi Z
Linearity	± 10% max

PIN	FUNCTION
1	Voltage Control Vc
2	NC or Tri-state
3	GND/Case
4	Output
5	NC
6	Vdd

MARKING:

- XX.X -A (Frequency); A - Tri-state option
- ASLV ZY (Z: month A to L; Y: year 0 for 2000, 1 for 2001)

OPTIONS AND PART IDENTIFICATION (Left blank if standard):

ASLV - Frequency - Temperature - Duty cycle - Tri-state - Packaging

Temperature options:

- D for -10°C to +60°C
- E for -20°C to +70°C
- F for -30°C to +70°C

Symmetry option:

- S for 45/55% at 1/2Vdd

Tri-state mode option:

- A for tristate

Packaging option:

- T for Tape and Reel (1,000pcs/reel)

OUTLINE DRAWING:

