



# SAW Components

Data Sheet B7709





SAW Components

B7709

Low-Loss Filter for Mobile Communication

1960,0 MHz

Data Sheet




Chip Sized SAW Package DCS6I

**Features**

- Low-loss RF filter for mobile telephone PCS systems, receive path
- High selectivity
- Low amplitude ripple
- Usable passband 60 MHz
- Unbalanced to balanced operation
- No external matching required
- Package for **Surface Mounted Technology (SMT)**

**Terminals**


- Gold-plated Ni



Dimensions in mm, approx. weight 0,014 g

**Pin configuration**

- 2 Input
- 4, 6 Balanced output
- 1, 3, 5 To be grounded



Type	Ordering code	Marking and Package according to	Packing according to
B7709	B39202-B7709-C610	C61157-A7-A76	F61074-V8112-Z000

Electrostatic Sensitive Device (ESD)

**Maximum ratings**

Operable temperature range	$T$	- 30 / + 85	°C	
Storage temperature range	$T_{stg}$	- 40 / + 85	°C	
DC voltage	$V_{DC}$	5	V	
ESD voltage	$V_{ESD}$	50	V	
Input power max.				
880 ... 915 MHz	$P_{IN}$	13	dBm	source and load impedance 50 $\Omega$ peak power of GSM signal, duty cycle 2 : 8
1710 ... 1785 MHz		13	dBm	
1850 ... 1910 MHz		13	dBm	
elsewhere		0	dBm	continuous wave



Data Sheet



Characteristics

Operating Temperature Range:  $T = +25 \pm 2^\circ\text{C}$   
 Terminating source impedance:  $Z_S = 50 \Omega$  (unbalanced)  
 Terminating load impedance:  $Z_L = 50 \Omega$  (balanced)

			min.	typ.	max.	
<b>Center frequency</b>	$f_C$		—	1960,0	—	MHz
<b>Maximum insertion attenuation</b>	$\alpha_{\max}$	1930,0 ... 1990,0 MHz	—	3,5	3,9	dB
<b>Amplitude ripple (p-p)</b>	$\Delta\alpha$	1930,0 ... 1990,0 MHz	—	1,1	1,5	dB
<b>Input VSWR</b>		1930,0 ... 1990,0 MHz	—	2,0	2,2	
<b>Output VSWR</b>		1930,0 ... 1990,0 MHz	—	2,0	2,2	
<b>Differential to common mode suppression</b>	$S_{sc12}$	1930,0 ... 1990,0 MHz	—	18	—	dB
		855,0 ... 995,0 MHz	—	29	—	dB
		1710,0 ... 1990,0 MHz	—	18	—	dB
		3420,0 ... 3980,0 MHz	—	29	—	dB
<b>Attenuation</b>	$\alpha$	0,0 ... 1600,0 MHz	35	38	—	dB
		1600,0 ... 1830,0 MHz	23	28	—	dB
		1830,0 ... 1910,0 MHz	12	15	—	dB
		2010,0 ... 2070,0 MHz	12	20	—	dB
		2070,0 ... 3500,0 MHz	23	25	—	dB
		3500,0 ... 4000,0 MHz	20	22	—	dB
		4000,0 ... 6000,0 MHz	15	16	—	dB



Data Sheet



Characteristics

Operating Temperature Range:  $T = -10$  to  $+80^{\circ}\text{C}$   
 Terminating source impedance:  $Z_S = 50\ \Omega$  (unbalanced)  
 Terminating load impedance:  $Z_L = 50\ \Omega$  (balanced)

		min.	typ.	max.	
<b>Center frequency</b>	$f_C$	—	1960,0	—	MHz
<b>Maximum insertion attenuation</b>	$\alpha_{\max}$	—	3,7	4,4	dB
1930,0 ... 1990,0 MHz					
<b>Amplitude ripple (p-p)</b>	$\Delta\alpha$	—	1,3	2,0	dB
1930,0 ... 1990,0 MHz					
<b>Input VSWR</b>		—	2,1	2,3	
1930,0 ... 1990,0 MHz					
<b>Output VSWR</b>		—	2,1	2,3	
1930,0 ... 1990,0 MHz					
<b>Differential to common mode suppression</b>	$S_{sc12}$	—	18	—	dB
1930,0 ... 1990,0 MHz					
855,0 ... 995,0 MHz			29	—	
1710,0 ... 1990,0 MHz			18	—	
3420,0 ... 3980,0 MHz			29	—	
<b>Attenuation</b>	$\alpha$				
0,0 ... 1600,0 MHz		35	38	—	dB
1600,0 ... 1830,0 MHz		23	28	—	dB
1830,0 ... 1910,0 MHz		8	13	—	dB
2010,0 ... 2070,0 MHz		9	15	—	dB
2070,0 ... 3500,0 MHz		23	25	—	dB
3500,0 ... 4000,0 MHz		20	22	—	dB
4000,0 ... 6000,0 MHz		15	16	—	dB



Data Sheet




Characteristics

Operating Temperature Range:  $T = -30$  to  $+85^{\circ}\text{C}$   
 Terminating source impedance:  $Z_S = 50\ \Omega$  (unbalanced)  
 Terminating load impedance:  $Z_L = 50\ \Omega$  (balanced)


		min.	typ.	max.	
<b>Center frequency</b>	$f_C$	—	1960,0	—	MHz
<b>Maximum insertion attenuation</b>	$\alpha_{\max}$				
1930,0 ... 1990,0	MHz	—	3,8	4,6	dB
<b>Amplitude ripple (p-p)</b>	$\Delta\alpha$				
1930,0 ... 1990,0	MHz	—	1,3	2,2	dB
<b>Input VSWR</b>					
1930,0 ... 1990,0	MHz	—	2,1	2,3	
<b>Output VSWR</b>					
1930,0 ... 1990,0	MHz	—	2,1	2,3	
<b>Differential to common mode suppression</b>	$S_{sc12}$				
1930,0 ... 1990,0	MHz	—	18	—	dB
855,0 ... 995,0	MHz	—	29	—	dB
1710,0 ... 1990,0	MHz	—	18	—	dB
3420,0 ... 3980,0	MHz	—	29	—	dB
<b>Attenuation</b>	$\alpha$				
0,0 ... 1600,0	MHz	35	38	—	dB
1600,0 ... 1830,0	MHz	23	28	—	dB
1830,0 ... 1910,0	MHz	7	12	—	dB
2010,0 ... 2070,0	MHz	7	14	—	dB
2070,0 ... 3500,0	MHz	23	25	—	dB
3500,0 ... 4000,0	MHz	20	22	—	dB
4000,0 ... 6000,0	MHz	15	16	—	dB



Transfer function



Transfer function (wide band)





**SAW Components**

**B7709**

**Low-Loss Filter for Mobile Communication**

**1960,0 MHz**

Data Sheet



**Published by EPCOS AG**

**Surface Acoustic Wave Components Division, SAW MC WT**

**P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.