

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311


Phone: (818) 701-4933 Fax: (818) 701-4939

BAV70WT

Features

- Power dissipation: 200mW (T_{amb}=25℃)
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- For Surface Mount Application

Marking KJA




Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C

Electrical Characteristics @ 25°C Unless Otherwise Specified

Reverse Voltage	V_R	75V	I _R =100 μ A	
Peak Forward	I _F	150mA		
Current				
Maximum		0.715V	I _{FM} =1mA;	
Instantaneous	V_{F}	0.855	I _{FM} =10mA;	
Forward Voltage		1.0V	I _{FM} =50mA;	
		1.25V	I _{FM} =150mA;	
Maximum DC				
Reverse Current At	I_R	2.5μΑ	V _R =75Volts	
Rated DC Blocking				
Voltage				
Diode Capacitance	C_D	2pF	Measured at 1.0MHz,	
			V _R =0V	
Reverse Recovery	T_{rr}	4ns	$I_F=I_R=10mA$	
Time			Irr=0.1I _R	
			R _L =100 Ω	

200mW Switching Diode



DIMENSIONS						
	INCHES		MM			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.071	.087	1.80	2.20		
В	.045	.053	1.15	1.35		
С	.079	.087	2.00	2.20		
D	.026 Nominal		0.65Nominal			
Е	.047	.055	1.20	1.40		
F	.012	.016	.30	.40		
G	.000	.004	.000	.100		
Н	.035	.039	.90	1.00		
J	.004	.010	.100	.250		
K	.012	.016	.30	.40		

Suggested Solder
Pad Layout

0.70

1.90

1.90

0.65

0.65



Micro Commercial Components

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.