

FAIRCHILD

A Schlumberger Company

BAX13

High Speed Switching Diode

T-03-09

- C...3.0 pF (MAX)
- t_{rr}...4.0 ns (MAX)

PACKAGE

BAX13

DO-35

ABSOLUTE MAXIMUM RATINGS (Note 1)**Temperatures**

Storage Temperature Range	-65°C to +200°C
Maximum Operating Junction Temperature	+175°C
Lead Temperature	+260°C

Power Dissipation (Note 2)

Maximum Total Dissipation at 25°C Ambient	500 mW
Linear Derating Factor (from 25°C)	3.33 mW / °C

Maximum Voltages and Currents

V _{RRM}	Repetitive Peak Reverse Voltage	50 V
V _R	Reverse Voltage	50 V
I _O	Average Rectified Current	100 mA
I _F	Forward Current	300 mA
I _f	Recurrent Peak Forward Current	400 mA
I _{FSM}	Peak Forward Surge Current	
	Pulse Width = 1.0 s	1.0 A
	Pulse Width = 1.0 μs	4.0 A

ELECTRICAL CHARACTERISTICS (25°C Ambient Temperature unless otherwise noted)

SYMBOL	CHARACTERISTIC	MIN	MAX	UNITS	TEST CONDITIONS
V _F	Forward Voltage	0.7 0.8 1.0 1.53		V	I _F = 2.0 mA I _F = 10 mA, T _A = 100°C I _F = 20 mA I _F = 75 mA.
I _R	Reverse Current	25 10 50 200 25		nA μA nA nA μA	V _R = 10 V V _R = 10 V, T _A = 150°C V _R = 25 V V _R = 50 V V _R = 60 V, T _A = 150°C
C	Capacitance		3.0	pF	V _R = 0, f = 1.0 MHz
t _{rr}	Reverse Recovery Time		4.0	ns	I _f = 10 mA, V _r = 6.0 V, R _L = 100Ω, I _f = 1.0 mA
Q _S	Recovered Charge		45	pC	I _f = 10 mA, V _r = 5.0 V, R _L = 500Ω

NOTES:

1. These ratings are limiting values above which the serviceability of any individual semiconductor device may be impaired.
2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.
3. For product family characteristic curves, refer to Chapter 4, D4.