



STANDARD CHIP LED LAMPS



BL-HXXX5 (0805) Series

NOTE:

- All dimensions are in millimeters (inches).
- Tolerance is $\pm 0.10(.004)$ unless otherwise specified.
- Specifications are subject to change without notice.
- Condition for IFp is pulse of 1/10 duty and 0.1msec width.

Absolute Maximum Ratings (Ta=25°C)

	UNIT	SPEC.
IF	mA	30
IFp	mA	100
V _R	V	5
IR	uA	100
Top	°C	-25~+80
Tstg	°C	-30~+85

Part No.	Chip				Lens Appearance	Electro-optical Data (At 20mA)				Viewing Angle 2θ 1/2 (deg)±5
	Material	Emitted Color	λ _p (nm)	Δλ (nm)		V _f (V)		I _v (mcd)		
						Typ.	Max.	Min.	Typ.	
BL-HH035	GaP/GaP	Bright Red	700	90	Water Clear	2.2	2.6	0.4	1.2	120
BL-HG035	GaP/GaP	Green	568	30		2.2	2.6	4.0	12.0	
BL-HGC35	GaP/GaP	Green	568	30		2.1	2.6	5.0	15.0	
BL-HX135	GaP/GaP	Hi-Eff Green	568	30		2.0	2.6	5.5	17.0	
BL-HW135	GaP/GaP	Pure Green	555	25		2.2	2.6	1.0	3.0	
BL-HY035	GaAsP/GaP	Yellow	585	35		2.1	2.6	1.5	5.0	
BL-HE035	GaAsP/GaP	Hi-Eff Red	630	45		2.0	2.6	2.5	7.0	
BL-HE135	GaAsP/GaP	Hi-Eff Red	640	45		2.0	2.6	2.5	7.0	
BL-HA135	GaAsP/GaP	Soft-Orange	610	35		2.0	2.6	1.5	5.0	
* BL-HS035	GaAlAs/GaAs	Super Red	660	20		1.7	2.6	4.0	12.0	
* BL-HS135	GaAlAs/GaAs	Super Red	660	20		1.8	2.6	3.0	9.0	
* BL-HD035	GaAlAs/GaAs	Super Red	660	20		1.8	2.6	6.5	20.0	
* BL-HF035	GaAlAs/GaAlAs	Super Red	660	20		2.1	2.6	10.0	30.0	
* BL-HF135	GaAlAs/GaAlAs	Super Red	660	20		2.1	2.6	13.5	40.0	
* BL-HF535	GaAlAs/GaAlAs	Super Red	660	20		2.2	2.6	9.5	28.0	