

# BUK7208-40B

TrenchMOS™ standard level FET

Rev. 02 — 22 January 2004

Product data

## 1. Product profile

### 1.1 Description

N-channel enhancement mode field-effect power transistor in a plastic package using Philips High-Performance Automotive (HPA) TrenchMOS™ technology.

### 1.2 Features

- Very low on-state resistance
- 185 °C rated
- Q101 compliant
- Standard level compatible.

### 1.3 Applications



- Automotive systems
- Motors, lamps and solenoids
- 12 V loads
- General purpose power switching.

### 1.4 Quick reference data

- $E_{DS(AL)S} \leq 242 \text{ mJ}$
- $I_D \leq 75 \text{ A}$
- $R_{DSon} = 6.6 \text{ m}\Omega \text{ (typ)}$
- $P_{tot} \leq 167 \text{ W}$ .

## 2. Pinning information

Table 1: Pinning - SOT428 (D-PAK), simplified outline and symbol

Pin	Description	Simplified outline	Symbol
1	gate (g)		
2	drain (d)	[1]	
3	source (s)		
mb	mounting base; connected to drain (d)	 Top view MBK091	 MBB076

[1] It is not possible to make connection to pin 2 of the SOT428 package.



PHILIPS

### 3. Ordering information

**Table 2: Ordering information**

Type number	Package			Version
	Name	Description		
BUK7208-40B	D-PAK	Plastic single-ended surface mounted package (Philips version of D-PAK); 3 leads (one lead cropped).		SOT428

### 4. Limiting values


**Table 3: Limiting values**

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
$V_{DS}$	drain-source voltage (DC)		-	40	V
$V_{DGR}$	drain-gate voltage (DC)	$R_{GS} = 20 \text{ k}\Omega$	-	40	V
$V_{GS}$	gate-source voltage (DC)		-	$\pm 20$	V
$I_D$	drain current (DC)	$T_{mb} = 25^\circ\text{C}; V_{GS} = 10 \text{ V};$ <a href="#">Figure 2 and 3</a>	[1] -	105	A
			[2] -	75	A
		$T_{mb} = 100^\circ\text{C}; V_{GS} = 10 \text{ V};$ <a href="#">Figure 2</a>	[2] -	75	A
$I_{DM}$	peak drain current	$T_{mb} = 25^\circ\text{C};$ pulsed; $t_p \leq 10 \mu\text{s};$ <a href="#">Figure 3</a>	-	420	A
$P_{tot}$	total power dissipation	$T_{mb} = 25^\circ\text{C};$ <a href="#">Figure 1</a>	-	167	W
$T_{stg}$	storage temperature		-55	+185	$^\circ\text{C}$
$T_j$	junction temperature		-55	+185	$^\circ\text{C}$
<b>Source-drain diode</b>					
$I_{DR}$	reverse drain current (DC)	$T_{mb} = 25^\circ\text{C}$	[1] -	105	A
			[2] -	75	A
$I_{DRM}$	peak reverse drain current	$T_{mb} = 25^\circ\text{C};$ pulsed; $t_p \leq 10 \mu\text{s}$	-	420	A
<b>Avalanche ruggedness</b>					
$E_{DS(AL)S}$	non-repetitive drain-source avalanche energy	unclamped inductive load; $I_D = 75 \text{ A};$ $V_{DS} \leq 40 \text{ V}; V_{GS} = 10 \text{ V};$ $R_{GS} = 50 \Omega;$ starting $T_j = 25^\circ\text{C}$	-	242	mJ


[1] Current is limited by power dissipation chip rating.

[2] Continuous current is limited by package.




$$P_{der} = \frac{P_{tot}}{P_{tot}(25^{\circ}\text{C})} \times 100\%$$

**Fig 1.** Normalized total power dissipation as a function of mounting base temperature.



$V_{GS} \geq 10$  V

**Fig 2.** Continuous drain current as a function of mounting base temperature.



$T_{mb} = 25$  °C;  $I_{DM}$  single pulse.


**Fig 3.** Safe operating area; continuous and peak drain currents as a function of drain-source voltage.

## 5. Thermal characteristics

**Table 4: Thermal characteristics**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$R_{th(j-a)}$	thermal resistance from junction to ambient		-	71.4	-	K/W
$R_{th(j-mb)}$	thermal resistance from junction to mounting base	Figure 4	-	-	0.95	K/W

### 5.1 Transient thermal impedance




**Fig 4.** Transient thermal impedance from junction to mounting base as a function of pulse duration.

## 6. Characteristics


**Table 5: Characteristics** $T_j = 25^\circ\text{C}$  unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
<b>Static characteristics</b>						
$V_{(\text{BR})\text{DSS}}$	drain-source breakdown voltage	$I_D = 0.25 \text{ mA}; V_{GS} = 0 \text{ V}$ $T_j = 25^\circ\text{C}$ $T_j = -55^\circ\text{C}$	40	-	-	V
$V_{GS(\text{th})}$	gate-source threshold voltage	$I_D = 1 \text{ mA}; V_{DS} = V_{GS}$ ; Figure 9 $T_j = 25^\circ\text{C}$ $T_j = 185^\circ\text{C}$ $T_j = -55^\circ\text{C}$	2	3	4	V
$I_{DSS}$	drain-source leakage current	$V_{DS} = 40 \text{ V}; V_{GS} = 0 \text{ V}$ $T_j = 25^\circ\text{C}$ $T_j = 185^\circ\text{C}$	-	0.02	1	$\mu\text{A}$
$I_{GSS}$	gate-source leakage current	$V_{GS} = \pm 20 \text{ V}; V_{DS} = 0 \text{ V}$	-	2	100	nA
$R_{DS\text{on}}$	drain-source on-state resistance	$V_{GS} = 10 \text{ V}; I_D = 25 \text{ A}$ ; Figure 7 and 8 $T_j = 25^\circ\text{C}$ $T_j = 185^\circ\text{C}$	-	6.6	8	$\text{m}\Omega$
<b>Dynamic characteristics</b>						
$Q_{g(\text{tot})}$	total gate charge	$V_{GS} = 10 \text{ V}; V_{DS} = 32 \text{ V}$	-	35	-	nC
$Q_{gs}$	gate-source charge	$I_D = 25 \text{ A}$ ; Figure 14	-	9.8	-	nC
$Q_{gd}$	gate-drain (Miller) charge		-	11.5	-	nC
$C_{iss}$	input capacitance	$V_{GS} = 0 \text{ V}; V_{DS} = 25 \text{ V}$	-	1870	2493	pF
$C_{oss}$	output capacitance	$f = 1 \text{ MHz}$ ; Figure 12	-	482	578	pF
$C_{rss}$	reverse transfer capacitance		-	201	275	pF
$t_{d(\text{on})}$	turn-on delay time	$V_{DS} = 30 \text{ V}; R_L = 1.2 \Omega$	-	16	-	nS
$t_r$	rise time	$V_{GS} = 10 \text{ V}; R_G = 10 \Omega$	-	104	-	nS
$t_{d(\text{off})}$	turn-off delay time		-	47	-	nS
$t_f$	fall time		-	51	-	nS
$L_d$	internal drain inductance	measured from drain to center of die	-	2.5	-	nH
$L_s$	internal source inductance	measured from source lead to source bond pad	-	7.5	-	nH
<b>Source-drain diode</b>						
$V_{SD}$	source-drain (diode forward) voltage	$I_S = 17 \text{ A}; V_{GS} = 0 \text{ V}$ ; Figure 15	-	0.85	1.2	V
$t_{rr}$	reverse recovery time	$I_S = 20 \text{ A}; dI_S/dt = -100 \text{ A}/\mu\text{s}$	-	50	-	ns
$Q_r$	recovered charge	$V_{GS} = -10 \text{ V}; V_{DS} = 30 \text{ V}$	-	36	-	nC




$T_j = 25^\circ\text{C}; t_p = 300 \mu\text{s}$

**Fig 5. Output characteristics: drain current as a function of drain-source voltage; typical values.**




$T_j = 25^\circ\text{C}; I_D = 25 \text{ A}$

**Fig 6. Drain-source on-state resistance as a function of gate-source voltage; typical values.**




$T_j = 25^\circ\text{C}; t_p = 300 \mu\text{s}$

**Fig 7. Drain-source on-state resistance as a function of drain current; typical values.**




$$a = \frac{R_{DSon}}{R_{DSon}(25^\circ\text{C})}$$

**Fig 8. Normalized drain-source on-state resistance factor as a function of junction temperature.**




$I_D = 1 \text{ mA}; V_{DS} = V_{GS}$

**Fig 9. Gate-source threshold voltage as a function of junction temperature.**




$T_j = 25 \text{ }^{\circ}\text{C}; V_{DS} = V_{GS}$

**Fig 10. Sub-threshold drain current as a function of gate-source voltage.**




$T_j = 25 \text{ }^{\circ}\text{C}; V_{DS} = 25 \text{ V}$

**Fig 11. Forward transconductance as a function of drain current; typical values.**




$V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}$

**Fig 12. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values.**




$V_{DS} = 25 \text{ V}$

**Fig 13. Transfer characteristics: drain current as a function of gate-source voltage; typical values.**



$T_j = 25^\circ\text{C}; I_D = 25 \text{ A}$

**Fig 14. Gate-source voltage as a function of gate charge; typical values.**




$V_{GS} = 0 \text{ V}$

**Fig 15. Source (diode forward) current as a function of source-drain (diode forward) voltage; typical values.**

## 7. Package outline

Plastic single-ended surface mounted package (Philips version of D-PAK); 3 leads  
(one lead cropped)

SOT428



0      10      20 mm  
scale

**DIMENSIONS (mm are the original dimensions)**

UNIT	A	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub>	b	b <sub>1</sub>	b <sub>2</sub>	c	D	D <sub>1</sub> min.	E	E <sub>1</sub>	e	e <sub>1</sub>	H <sub>E</sub>	L	L <sub>1</sub> min.	L <sub>2</sub>	w	y max.
mm	2.38	0.65	0.93	0.89	1.1	5.46	0.4	6.22	4.0	6.73	4.81	2.285	4.57	10.4	2.95	0.5	0.9	0.2	0.2
	2.22	0.45	0.73	0.71	0.9	5.26	0.2	5.98		6.47	4.45			9.6	2.55		0.5		

**Note**

1. Measured from heatsink back to lead.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT428		TO-252	SC-63			-99-09-13 01-12-11

**Fig 16. SOT428 (D-PAK).**

## 8. Revision history

Table 6: Revision history

Rev	Date	CPCN	Description
02	20040122	-	Product data (9397 750 12228)
01	20021212	-	Objective data (9397 750 10806)

## 9. Data sheet status

Level	Data sheet status <sup>[1]</sup>	Product status <sup>[2][3]</sup>	Definition
I	Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
II	Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
III	Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN).

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

## 10. Definitions

**Short-form specification** — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

**Limiting values definition** — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Application information** — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

**Right to make changes** — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no licence or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

## 12. Trademarks

TrenchMOS — is a trademark of Koninklijke Philips Electronics N.V.

## 11. Disclaimers

**Life support** — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors

## Contact information

For additional information, please visit <http://www.semiconductors.philips.com>.

For sales office addresses, send e-mail to: [sales.addresses@www.semiconductors.philips.com](mailto:sales.addresses@www.semiconductors.philips.com).

Fax: +31 40 27 24825

9397 750 12228

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.

## Contents

<b>1</b>	<b>Product profile</b>	<b>1</b>
1.1	Description	1
1.2	Features	1
1.3	Applications	1
1.4	Quick reference data	1
<b>2</b>	<b>Pinning information</b>	<b>1</b>
<b>3</b>	<b>Ordering information</b>	<b>2</b>
<b>4</b>	<b>Limiting values</b>	<b>2</b>
<b>5</b>	<b>Thermal characteristics</b>	<b>4</b>
5.1	Transient thermal impedance	4
<b>6</b>	<b>Characteristics</b>	<b>5</b>
<b>7</b>	<b>Package outline</b>	<b>9</b>
<b>8</b>	<b>Revision history</b>	<b>10</b>
<b>9</b>	<b>Data sheet status</b>	<b>11</b>
<b>10</b>	<b>Definitions</b>	<b>11</b>
<b>11</b>	<b>Disclaimers</b>	<b>11</b>
<b>12</b>	<b>Trademarks</b>	<b>11</b>

© Koninklijke Philips Electronics N.V. 2004.

Printed in The Netherlands

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Date of release: 22 January 2004

Document order number: 9397 750 12228



**PHILIPS**

*Let's make things better.*