


Features

- High Cell Density DMOS Technology
- Low On-State Resistance
- High Power and Current Capability
- Fast Switching Speed
- High Transient Tolerance



SOT-223		
Dim	Min	Max
A	6.30	6.71
B	2.90	3.10
C	6.71	7.29
D	3.30	3.71
E	2.22	2.35
G	0.92	1.00
H	1.10	1.30
J	1.55	1.80
K	0.025	0.102
L	0.66	0.79
M	4.55	4.70
N	—	10°
P	10°	16°
R	0.254	0.356
S	10°	16°

All Dimensions in mm

Mechanical Data

- SOT-223 Plastic Case
- Terminal Connections: See Outline Drawing and Internal Circuit Diagram Above

Maximum Ratings

25°C unless otherwise specified

Characteristic	Symbol	Value	Unit
Drain-Source Voltage	V _{DSS}	-30	V
Gate-Source Voltage	V _{GSS}	±20	V
Drain Current Note 1a Continuous Pulsed	I _D	±5.9 ±15	A
Maximum Power Dissipation Note 1 a Note 1 b Note 1 c	P _d	3.0 1.3 1.1	W
Operating and Storage Temperature Range	T _j , T _{STG}	-65 to +150	°C

Thermal Characteristics

Characteristic	Symbol	Value	Unit
Thermal Resistance, Junction-to-Ambient Note 1	R _{θJA}	42	°C/W
Thermal Resistance, Junction-to-Case	R _{θJC}	12	°C/W





Notes:



1. R_{θJA} is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. R_{θJC} is guaranteed by design while R_{θCA} is determined by the user's board design.
 - With 1 in² oz 2 oz. copper mounting pad R_{θJA} = 42°C/W.
 - With 0.0066 in² oz 2 oz. copper mounting pad R_{θJA} = 95°C/W.
 - With 0.0123 in² oz 2 oz. copper mounting pad R_{θJA} = 110°C/W.

Electrical Characteristics^{25°C unless otherwise specified}

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	V_{DSS}	-30	—	—	V	$V_{GS} = 0V, I_D = -250\mu A$
Zero Gate Voltage Drain Current $T_j = 70^\circ C$	I_{DSS}	—	—	-1.0 -5.0	μA	$V_{DS} = -24V, V_{GS} = 0V$ $V_{DS} = -15V, V_{GS} = 0V$
Gate-Body Leakage, Forward	I_{GSSF}	—	—	100	nA	$V_{GS} = 20V, V_{DS} = 0V$
Gate-Body Leakage, Reverse	I_{GSSR}	—	—	-100	nA	$V_{GS} = -20V, V_{DS} = 0V$
ON CHARACTERISTICS (Note 2)						
Gate Threshold Voltage	$V_{GS(th)}$	-1.0	-2.7	—	V	$V_{DS} = V_{GS}, I_D = -250\mu A$
Static Drain-Source On-Resistance $T_j = 125^\circ C$	$R_{DS(on)}$	—	0.038 0.046 0.064	0.05 0.07 0.09	Ω	$V_{GS} = -10V, I_D = -5.9A$ $V_{GS} = -6.0V, I_D = -5.2A$ $V_{GS} = -4.5V, I_D = -4.6A$
On-State Drain Current	$I_{D(on)}$	-15 -5.0	—	—	A	$V_{GS} = -10V, V_{DS} = -5.0V$ $V_{GS} = -4.5V, V_{DS} = -5.0V$
Forward Transconductance	g_{FS}	—	10	—	m	$V_{DS} = -15V, I_D = -5.9A$
DYNAMIC CHARACTERISTICS						
Input Capacitance	C_{iss}	—	950	—	pF	$V_{DS} = -15V, V_{GS} = 0V$ $f = 1.0MHz$
Output Capacitance	C_{oss}	—	610	—	pF	
Reverse Transfer Capacitance	C_{rss}	—	220	—	pF	
SWITCHING CHARACTERISTICS (Note 2)						
Turn-On Delay Time	$t_{D(on)}$	—	10	30	ns	$V_{DD} = -15V, I_D = -1.0A$ $V_{GEN} = -10V, R_{GEN} = 6.0\Omega$
Turn-On Rise Time	t_r	—	18	60	ns	
Turn-Off Delay Time	$t_{D(off)}$	—	80	120	ns	
Turn-Off Fall Time	t_f	—	45	100	ns	
Total Gate Charge	Q_g	—	29	40	nC	$V_{DS} = -15V, I_D = -5.9A$ $V_{GS} = -10V$
Gate-Source Charge	Q_{gs}	—	3.0	—	nC	
Gate-Drain Charge	Q_{gd}	—	11	—	nC	
DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS						
Max Continuous Drain-Source Diode Forward Current	I_S	—	—	-1.9	A	
Drain-Source Diode Forward Voltage	V_{SD}	—	-0.85	-1.3	V	$V_{GS} = 0V, I_S = -5.9A$ (Note 2)
Reverse Recovery Time	t_{rr}	—	—	100	ns	$V_{GS} = 0V, I_F = -5.9A$ $dI_F/dt = 100 A/\mu s$

Notes: 2. Pulse Test: Pulse width $> 300\mu s$, duty cycle $< 2.0\%$.





Remark: Thermal characterization performed under conditions described in note 1c. Transient thermal response will change depending on the circuit board design.