

# SPECIFICATION

Device Name : High Voltage Silicon Diode

Type Name : ESJA56-24A

Spec. No. :

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

Fuji Electric Co., Ltd.  
Matsumoto Factory

	DATE	NAME	APPROVED		<b>Fuji Electric Co., Ltd.</b>
DRAWN					
CHECKED					
				DWG. NO.	

## 1. SCOPE

This specification provide the ratings and the requirements for high voltage silicon diode ESJA56-24A made by FUJI ELECTRIC CO.,LTD.

## 2. OUT VIEW

Shape and dimensions are described in Fig.3.

## 3. IDENTIFICATION

The diode shall be marked with Cathode Mark and Lot No..

## 4. RATINGS AND CHARACTERISTICS

### 4.1 ABSOLUTE MAX. RATINGS. ( Ta=25 °C unless otherwise noted. )

Items	Conditions	Symbols	Ratings	Units
Repetitive peak reverse voltage.		$V_{RRM}$	24	kVpeak
Non-Repetitive peak forward current.	50Hz Sine-half wave peak value	$I_{FSM}$	0.5	Apeak
Average forward current.	50Hz Sine Wave	$I_{AV}$	5	mA
Allowable junction temperature.		$T_j$	120	°C
Storage temperature range.		$T_{stg}$	-40~120	°C
Allowable operating case temperature.		$T_c$	100	°C

### 4.2 ELECTRICAL CHARACTERISTICS ( Ta=25 °C unless otherwise noted. )

Items	Conditions	Symbols	Ratings	Units
Maximum forward voltage drop	$I_F=10mA$	$V_F$	90	V
Maximum reverse current	$V_R=24kV$	$I_{R1}$	2	$\mu A$
Maximum reverse current	$V_R=24kV, 100^\circ C$	$I_{R2}$	5	$\mu A$
Maximum reverse recovery time	$I_F=2mA, I_R=4mA$	$t_{rr}$	0.08	$\mu S$
Maximum junction capacitance	$f=1MHz, V_R=0V$	$C_j$	1	pF

### 4.3 MECHANICAL CHARACTERISTICS

Weight : Ca. 0.4 gr.

Vibration proof : 5 G

Fuji Electric Co.,Ltd

DWG NO.

H04-004-03






Fig.2 Reverse characteristic[VR-IR]




*Fig.1 Forward characteristic [VF-IF]*



*Fig.4 Reverse recovery time characteristic [Ta-trr]*

Typical




*Fig.3 Avalanche characteristic [ $V_Z$ - $I_Z$ ]*

Dimensions

Unit : mm

ESJA56-24A



For more information, contact:

**Collmer Semiconductor, Inc.**

P.O. Box 702708

Dallas, TX 75370

972-733-1700

972-381-9991 Fax

<http://www.collmer.com>