



Description








Mechanical Dimensions



Features

- **LOW COST**
- **HIGH SURGE CAPABILITY**
- **DIFFUSED JUNCTION**
- **LOW LEAKAGE CURRENT**
- **HIGH TEMPERATURE CAPABILITY**
- **MEETS UL SPECIFICATION 94V-0**

Electrical Characteristics @ 25°C.	FR2501 ... 2510 Series							Units
Maximum Ratings	FR2501	FR2502	FR2503	FR2504	FR2506	FR2508	FR2510	
Peak Repetitive Reverse Voltage... V_{RRM}	100	200	300	400	600	800	1000	Volts
RMS Reverse Voltage... $V_{R(rms)}$	70	140	210	280	420	560	700	Volts
DC Blocking Voltage... V_{DC}	100	200	300	400	600	800	1000	Volts
Average Forward Rectified Current... $I_{F(av)}$ $T_A = 55^\circ\text{C}$ (Note 3)				25				Amps
Non-Repetitive Peak Forward Surge Current... I_{FSM} @ Rated Current & Temp				400				Amps
Forward Voltage @ 80A... V_F	< 1.1 >		< 1.2 >					Volts
DC Reverse Current... I_R @ Rated DC Blocking Voltage, 150°C				2.0				μAmps
				250				μAmps
Typical Junction Capacitance... C_J (Note 1)	< 200 >		< 300 >					pF
Typical Thermal Resistance... $R_{\theta JC}$ (Note 2)				1.0				°C/W
Typical Reverse Recovery Time... t_{RR}				3.0				μS
Operating & Storage Temperature Range... T_J, T_{STRG}				-65 to 175				°C



Ratings at 25 Deg. C ambient temperature unless otherwise specified.

Single Phase Half Wave, 60 HZ Resistive or Inductive Load.

For Capacitive Load, Derate Current by 20%.

- NOTES:**
1. Measured @ 1 MHz and applied reverse voltage of 4.0V.
 2. Thermal Resistance Junction to Ambient, Jedec Method.
 3. When Mounted to heat sink, from body.