


MITSUBISHI Nch POWER MOSFET

FS14SM-18A

HIGH-SPEED SWITCHING USE




FS14SM-18A



- V_{DS} 900V
- $r_{DS(ON)}(MAX)$ 0.85Ω
- I_D 14A

OUTLINE DRAWING

Dimensions in mm



- ① GATE
- ② DRAIN
- ③ SOURCE
- ④ DRAIN

TO-3P

APPLICATION

SMPS, DC-DC Converter, battery charger, power supply of printer, copier, HDD, FDD, TV, VCR, personal computer etc.

MAXIMUM RATINGS (T_c = 25°C)

| Symbol | Parameter | Conditions | Ratings | Unit |
|-----------|---------------------------|---------------|------------|------|
| V_{DS} | Drain-source voltage | $V_{GS} = 0V$ | 900 | V |
| V_{GSS} | Gate-source voltage | $V_{DS} = 0V$ | ± 30 | V |
| I_D | Drain current | | 14 | A |
| I_{DM} | Drain current (Pulsed) | | 42 | A |
| P_D | Maximum power dissipation | | 275 | W |
| T_{ch} | Channel temperature | | -55 ~ +150 | °C |
| T_{stg} | Storage temperature | | -55 ~ +150 | °C |
| — | Weight | Typical value | 4.8 | g |





FS14SM-18A







HIGH-SPEED SWITCHING USE

ELECTRICAL CHARACTERISTICS (T_{ch} = 25°C)


| Symbol | Parameter | Test conditions | Limits | | | Unit |
|------------------------|----------------------------------|---|---|------|------|------|
| | | | Min. | Typ. | Max. | |
| V (BR) DSS | Drain-source breakdown voltage | I _D = 1mA, V _{GS} = 0V | 900 | — | — | V |
| V (BR) GSS | Gate-source breakdown voltage | I _{GS} = ±100μA, V _{DS} = 0V | ±30 | — | — | V |
| I _{GSS} | Gate-source leakage current | V _{GS} = ±25V, V _{DS} = 0V | — | — | ±10 | μA |
| I _{DSS} | Drain-source leakage current | V _{DS} = 900V, V _{GS} = 0V | — | — | 1 | mA |
| V _{GS} (th) | Gate-source threshold voltage | I _D = 1mA, V _{DS} = 10V | 2 | 3 | 4 | V |
| r _{DS} (ON) | Drain-source on-state resistance | I _D = 7A, V _{GS} = 10V | — | 0.63 | 0.85 | Ω |
| V _{DS} (ON) | Drain-source on-state voltage | I _D = 7A, V _{GS} = 10V | — | 4.41 | 5.95 | V |
| y _{fs} | Forward transfer admittance | I _D = 7A, V _{DS} = 10V | 9.0 | 15.0 | — | S |
| C _{iss} | Input capacitance | V _{DS} = 25V, V _{GS} = 0V, f = 1MHz | — | 2900 | — | pF |
| C _{oss} | Output capacitance | | — | 290 | — | pF |
| C _{rss} | Reverse transfer capacitance | | — | 50 | — | pF |
| t _d (on) | Turn-on delay time | V _{DD} = 200V, I _D = 7A, V _{GS} = 10V, R _{GEN} = R _{GS} = 50Ω | — | 45 | — | ns |
| t _r | Rise time | | — | 65 | — | ns |
| t _d (off) | Turn-off delay time | | — | 325 | — | ns |
| t _f | Fall time | | — | 100 | — | ns |
| V _{SD} | Source-drain voltage | | I _S = 7A, V _{GS} = 0V | — | 1.0 | 1.5 |
| R _{th} (ch-c) | Thermal resistance | Channel to case | — | — | 0.45 | °C/W |

PERFORMANCE CURVES







GATE-SOURCE VOLTAGE VS. GATE CHARGE (TYPICAL)




SOURCE-DRAIN DIODE FORWARD CHARACTERISTICS (TYPICAL)




ON-STATE RESISTANCE VS. CHANNEL TEMPERATURE (TYPICAL)



THRESHOLD VOLTAGE VS. CHANNEL TEMPERATURE (TYPICAL)



BREAKDOWN VOLTAGE VS. CHANNEL TEMPERATURE (TYPICAL)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS

