


# Spice Model



**M160UFG**



Part Number	Working Reverse Voltage (V <sub>rw</sub> )	Average Rectified Current (I <sub>o</sub> )		Reverse Current @ V <sub>rw</sub> (I <sub>r</sub> )		Forward Voltage (V <sub>f</sub> )		1 Cycle Surge Current t <sub>p</sub> =8.3ms (I <sub>fsm</sub> )	Repetitive Surge Current (I <sub>frm</sub> )	Reverse Recovery Time (3) (T <sub>rr</sub> )	Thermal Impedance J-L			Junction Cap. @50VDC @ 1kHz (C <sub>j</sub> )
		55°C(1)	100°C(2)	25°C	100°C	25°C					25°C	25°C	25°C	
	Volts	mAmps	mAmps	µA	µA	Volts	mA	Amps	Amps	ns	°C/W	°C/W	°C/W	pF
M160UFG	16000	10	5	0.1	10	35	10	1	2	100	33	45	65	0.5



Part	A
M25UFG M50UFG M100UFG	.300(7.62) MAX.
M160UFG	.350(8.89) MAX.

Parameter	Description	Value	Units
IS	Reverse leakage current	1.00E-07	Amps
N	Emission coefficient	65	
T	Temperature	25	C
RS	Diode series resistance	40	Ohm
TT	Transit time	70	nS
CJ0	Zero-bias junction capacitance	0.43	pF
VJ	Bulk junction potential	19.22	Volts
M	Grading coefficient	0.5	
EG	Energy-band gap	1.11	Volts
XTI	Temperature coefficient	3	
KF	Flicker-noise coefficient	0	
AF	Flicker-noise exponent	1	
FC	Coefficient for capacitance	0.5	
BV	Diode breakdown voltage	20000	Volts
IBV	Diode breakdown current	100	uAmps



**Voltage Multipliers, Inc.**  
8711 W. Roosevelt Ave.  
Visalia, CA 93291

Tel (559) 651-1402  
Fax (559) 651-0740  
www.voltagemultipliers.com