

MICRO


ELECTRONICS

5MM
OVAL TYPE
HIGH BRIGHTNESS
YELLOW GREEN LED LAMP

DESCRIPTION

MGB2310TK-X is a high brightness yellow green LED lamp encapsulated in a 5MM oval shape clear transparent lens.

3 brightness grouping is provide for customer's selection.



ABSOLUTE MAXIMUM RATINGS

Power Dissipation @ Ta=25°C
Forward Current, DC (IF)
Reverse Voltage
Operating Temperature Range
Storage Temperature Range
Lead Soldering Temperature (1/16" from body)

100mW
30mA
5V
-20 to +80°C
-30 to +100°C
260°C for 5 sec.

ELECTRO-OPTICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	CONDITIONS
Forward Voltage	VF		2.1	3.0	V	IF=20mA
Reverse Breakdown Voltage	BVR	5			V	IR=100μA
Luminous Intensity	IV	150	250		mcd	IF=20mA
		200	300			
		250	350			
Peak Wavelength	λp		570		nm	IF=20mA
Spectral Line Half Width	Δλ		30		nm	IF=20mA
Viewing Angle	2θ 1/2		100		degree	IF=20mA



MICRO ELECTRONICS LTD.

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.
Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex:43510 Micro Hx. Tel: 2343 0181-5

Dec-00